



RECOMMENDED HOLE LAYOUT

- ▲ .000100 BRIGHT TIN-LEAD OVER .000050 NICKEL.
- ▲ POINT OF MEASUREMENT FOR PLATING THICKNESS.
- ▲ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND THE HOUSING.
- ▲ ON ASSEMBLIES WITH FOUR OR MORE POSITIONS, TWO POLARIZATION SLOTS.
- ▲ ON ASSEMBLIES WITH TWO OR THREE POSITIONS, ONE POLARIZATION SLOT.
- ▲ SELECT POST TAILS FORMED TO PROVIDE CONNECTOR HOLD DOWN UNTIL SOLDERED. CONFIGURATION ACCEPTS 0.69[.027]-2.03[.080] THICK PRINTED CIRCUIT BOARD. (SEE DETAIL Z).
- ▲ .000100 BRIGHT TIN OVER .000050 NICKEL.
- ▲ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- ▲ .000100 MATTE TIN OVER .000050 NICKEL.
- ▲ HIGH TEMPERATURE CONFIGURATION.
- ▲ STANDOFFS NOT PRESENT ON UNDERSIDE OF ASSEMBLY
- ▲ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

- ▲ OBSOLETE
- ▲ OBSOLETE
- ▲ OBSOLETE
- ▲ OBSOLETE
- ▲ OBSOLETE
- ▲ OBSOLETE
- ▲ OBSOLETE
- ▲ OBSOLETE

REV	DATE	DESCRIPTION	BY	CHK	APP
▲	23.37	25.40	8	9	3-103669-0
▲	[.920]	[1.000]			
▲	8.13	10.16	2	3	2-103669-9
▲	[.320]	[.400]			
▲	15.75	17.78	5	6	2-103669-8
▲	[.620]	[.700]			
▲	13.21	15.24	4	5	2-103669-7
▲	[.520]	[.600]			
▲	10.67	12.70	3	4	2-103669-6
▲	[.420]	[.500]			
▲	5.59	7.62	1	2	2-103669-5
▲	[.220]	[.300]			
▲	64.01	66.04	24	25	2-103669-4
▲	[2.520]	[2.600]			
▲	61.47	63.50	23	24	2-103669-3
▲	[2.420]	[2.500]			
▲	58.93	60.96	22	23	2-103669-2
▲	[2.320]	[2.400]			
▲	56.39	58.42	21	22	2-103669-1
▲	[2.220]	[2.300]			
▲	53.85	55.88	20	21	2-103669-0
▲	[2.120]	[2.200]			
▲	51.31	53.34	19	20	1-103669-9
▲	[2.020]	[2.100]			
▲	48.77	50.80	18	19	1-103669-8
▲	[1.920]	[2.000]			
▲	46.23	48.26	17	18	1-103669-7
▲	[1.820]	[1.900]			
▲	43.69	45.72	16	17	1-103669-6
▲	[1.720]	[1.800]			
▲	41.15	43.18	15	16	1-103669-5
▲	[1.620]	[1.700]			
▲	38.61	40.64	14	15	1-103669-4
▲	[1.520]	[1.600]			
▲	36.07	38.10	13	14	1-103669-3
▲	[1.420]	[1.500]			
▲	33.53	35.56	12	13	1-103669-2
▲	[1.320]	[1.400]			
▲	30.99	33.02	11	12	1-103669-1
▲	[1.220]	[1.300]			
▲	28.45	30.48	10	11	1-103669-0
▲	[1.120]	[1.200]			
▲	25.91	27.94	9	10	103669-9
▲	[1.020]	[1.100]			
▲	23.37	25.40	8	9	103669-8
▲	[.920]	[1.000]			
▲	20.83	22.86	7	8	103669-7
▲	[.820]	[.900]			
▲	18.29	20.32	6	7	103669-6
▲	[.720]	[.800]			
▲	15.75	17.78	5	6	103669-5
▲	[.620]	[.700]			
▲	13.21	15.24	4	5	103669-4
▲	[.520]	[.600]			
▲	10.67	12.70	3	4	103669-3
▲	[.420]	[.500]			
▲	8.13	10.16	2	3	103669-2
▲	[.320]	[.400]			
▲	5.59	7.62	1	2	103669-1
▲	[.220]	[.300]			

THIS DRAWING IS A CONTROLLED DOCUMENT.		REVISED PER ECO-11-004587	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR
DESCRIPTION	TE Connectivity	TE Connectivity	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR
REVISED PER ECO-11-004587	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR		
DESCRIPTION	HDR ASSY, VERT, SINGLE ROW	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR	
REVISED PER ECO-11-004587	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR		
DESCRIPTION	HDR ASSY, VERT, SINGLE ROW	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR	
REVISED PER ECO-11-004587	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR		
DESCRIPTION	HDR ASSY, VERT, SINGLE ROW	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR	
REVISED PER ECO-11-004587	DATE	11-04-87	BY	11MM11	CHK	RK	APP	HMR		

OBSOLETE	△△△	△	64.01	66.04	24	25	7-103669-4
	△△△	△	[2,520]	[2,600]	23	24	7-103669-3
	△△△	△	58.93	60.96	22	23	7-103669-2
	△△△	△	[2,320]	[2,400]	21	22	7-103669-1
	△△△	△	56.39	58.42	20	21	7-103669-0
	△△△	△	[2,220]	[2,300]	19	20	6-103669-9
	△△△	△	53.85	55.88	18	19	6-103669-8
	△△△	△	[2,020]	[2,100]	17	18	6-103669-7
	△△△	△	48.77	50.80	16	17	6-103669-6
	△△△	△	[1,920]	[2,000]	15	16	6-103669-5
	△△△	△	43.69	45.72	14	15	6-103669-4
	△△△	△	[1,720]	[1,800]	13	14	6-103669-3
	△△△	△	41.15	43.18	12	13	6-103669-2
	△△△	△	[1,620]	[1,700]	11	12	6-103669-1
	△△△	△	38.61	40.64	10	11	6-103669-0
	△△△	△	[1,520]	[1,600]	9	10	5-103669-9
	△△△	△	36.07	38.10	8	9	5-103669-8
	△△△	△	[1,420]	[1,500]	7	8	5-103669-7
	△△△	△	33.53	35.56	6	7	5-103669-6
	△△△	△	[1,320]	[1,400]	5	6	5-103669-5
△△△	△	30.99	33.02	4	5	5-103669-4	
△△△	△	[1,220]	[1,300]	3	4	5-103669-3	
△△△	△	28.45	30.48	2	3	5-103669-2	
△△△	△	[1,120]	[1,200]	1	2	5-103669-1	
△△△	△	25.91	27.94				
△△△	△	[1,020]	[1,100]				
△△△	△	23.37	25.40				
△△△	△	[920]	[1,000]				
△△△	△	20.83	22.86				
△△△	△	[820]	[900]				
△△△	△	18.29	20.32				
△△△	△	[720]	[800]				
△△△	△	15.75	17.78				
△△△	△	[620]	[700]				
△△△	△	13.21	15.24				
△△△	△	[520]	[600]				
△△△	△	10.67	12.70				
△△△	△	[420]	[500]				
△△△	△	8.13	10.16				
△△△	△	[320]	[400]				
△△△	△	5.59	7.62				
△△△	△	[220]	[300]				
REMARKS	PLATING	C	B	A	NO. OF POSN	PART NO.	

△△ OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT. **TE Connectivity**

DATE: 108-25034
 DATE: 114-25026
 DATE: 100779

DESCRIPTION: HDR ASSY, VERT, SINGLE ROW
 WITH PL26 AMP/KOUDU MTE

SIZE: 2.54 [100] C/A 0.64 [025] SQ POST
 WITH PL26 AMP/KOUDU MTE

REVISIONS: 4, 1, 2, 2, AA2