

4


3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	BY	APPD
		K2		REVISED PER ECO-11-005027	11MAR11	RK	HMR



PLATING	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP	
OBsolete	2	2.59	1.295	1-103653-1	12	6-103949-1
OBsolete	2	2.39	1.195	1-103653-0	11	6-103949-0
	2	2.19	1.095	103653-9	10	5-103949-9
	2	1.99	.995	103653-8	9	5-103949-8
	2	1.79	.895	103653-7	8	5-103949-7
	3	2.39	.795	103653-6	7	5-103949-6
	2	1.39	.695	103653-5	6	5-103949-5
	4	2.38	.595	103653-4	5	5-103949-4
	4	1.98	.495	103653-3	4	5-103949-3
	5	1.98	.395	103653-2	3	5-103949-2
	8	2.36	.295	103653-1	2	5-103949-1
OBsolete	2	2.59	1.295	1-103653-1	12	1-103949-1
OBsolete	2	2.39	1.195	1-103653-0	11	1-103949-0
	2	2.19	1.095	103653-9	10	103949-9
	2	1.99	.995	103653-8	9	103949-8
	2	1.79	.895	103653-7	8	103949-7
	3	2.39	.795	103653-6	7	103949-6
	2	1.39	.695	103653-5	6	103949-5
	4	2.38	.595	103653-4	5	103949-4
	4	1.98	.495	103653-3	4	103949-3
	5	1.98	.395	103653-2	3	103949-2
	8	2.36	.295	103653-1	2	103949-1

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103894
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 MATERIAL- HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR: BLACK PINS: PHOS. BRONZE
- 8 FINISH- PINS: .000030 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, OVER .000050 NICKEL.
- 9 FINISH- PINS: .000030 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, OVER .000050 NICKEL.
- 10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	OTHER DIMENSIONS: MILLIMETERS	DATE: 26JUL00	BY: R. BROWN
0 PLC 2 -	0 PLG 2 -	DATE: 26JUL00	CHK: K. WRIGHT
1 PLC 2 -	1 PLG 2 -	DATE: 26JUL00	APPD: K. WRIGHT
2 PLC 2 -	2 PLG 2 -	DATE: 26JUL00	NAME: SHROUDED PIN ASSY, AMPMODU MTE, SINGLE ROW, .100 CL, POLARIZED, W/ LATCH WINDOWS, FOR #26-#30 AWG WIRE SIZE, STRIP FORM
3 PLC 2 -	3 PLG 2 -	DATE: 26JUL00	PRODUCT SPEC: 108-25034
4 PLC 2 -	4 PLG 2 -	DATE: 26JUL00	APPLICATION SPEC: 114-25026
5 PLC 2 -	5 PLG 2 -	DATE: 26JUL00	SIZE: 108-25026
6 PLC 2 -	6 PLG 2 -	DATE: 26JUL00	RESTRICTED TO: A2 00779 C=103949
7 PLC 2 -	7 PLG 2 -	DATE: 26JUL00	CUSTOMER DRAWING

SCALE: 4:1 SHEET: 1 of 1 REV: K2

103949

A