






THIS DRAWING IS UNPUBLISHED
 UNLESS INDICATED OTHERWISE
 ALL RIGHTS RESERVED

REV	DATE	DESCRIPTION	BY	APP
AD	00	REVISED PER ECO-08-020774	27AUG99	KK AEG



RECOMMENDED HOLE PATTERN



DETAIL R

- △ CONTACT AREAS PLATED WITH .000030 GOLD, SOLDER TAILS PLATED WITH .000150 TIN-LEAD, ALL OVER .000050 NICKEL.
- △ POINT OF MEASUREMENT FOR GOLD THICKNESS IS .030 FROM MATING END OF CONTACT
- △ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- △ CONTACT AREAS PLATED WITH .000030 GOLD, SOLDER TAILS PLATED WITH .000150 TIN-LEAD, ALL OVER .000050 NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△ OBSOLETE	1.250	25	1.344	26	△ 6-104192-0
△ OBSOLETE	.600	13	.694	13	△ 5-104192-91
△ OBSOLETE	.200	4	.294	5	△ 5-104192-81
△ OBSOLETE	1.450	29	1.544	30	△ 5-104192-71
△ OBSOLETE	1.200	24	1.294	25	△ 5-104192-61
△ OBSOLETE	.950	19	1.044	20	△ 5-104192-51
△ OBSOLETE	.700	14	.794	15	△ 5-104192-41
△ OBSOLETE	.550	11	.644	12	△ 5-104192-31
△ OBSOLETE	.450	9	.544	10	△ 5-104192-21
△ OBSOLETE	1.250	25	1.344	26	△ 1-104192-01
△ OBSOLETE	.600	13	.694	13	△ 104192-9
△ OBSOLETE	.200	4	.294	5	△ 104192-8
△ OBSOLETE	1.450	29	1.544	30	△ 104192-7
△ OBSOLETE	1.200	24	1.294	25	△ 104192-6
△ OBSOLETE	.950	19	1.044	20	△ 104192-5
△ OBSOLETE	.700	14	.794	15	△ 104192-4
△ OBSOLETE	.550	11	.644	12	△ 104192-3
△ OBSOLETE	.450	9	.544	10	△ 104192-2
△ OBSOLETE	.350	7	.444	8	△ 104192-1

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE	ISSUED	BY	FOR
DATE	ISSUED	BY	FOR	REVISION	NO. OF POSN
108-1093	114-25031	A1	00779	104192	1
CUSTOMER DRAWING		DATE	REV	BY	APP
CUSTOMER DRAWING		DATE	REV	BY	APP