



- △ CONTACT AREA PLATED WITH .000762 [0.00030] MIN GOLD; SOLDER LEADS PLATED WITH .00381 [0.00150] MIN TIN-LEAD ALL OVER .00127 [0.00050] MIN NICKEL.
- △ POINT OF MEASUREMENT FOR PLATING THICKNESS
- △ DIMENSION APPLIES AT BASE OF SHROUD
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- △ (Z1) (Z2) ARE LOCATED THE SAME AS (Z7) (Z8) OPPOSITE SIDE OF HOUSING AS SHOWN
- △ HOUSING: THERMOPLASTIC, COLOR-BLACK. POSTS: COPPER ALLOY.
- △ CONTACT AREA PLATED WITH 0.000762 [0.00030] MIN GOLD, SOLDER LEADS PLATED WITH 0.00381 [0.00150] MIN TIN, ALL OVER 0.00127 [0.00050] MIN NICKEL.
- △ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- △ ROHS 2002/95/EC COMPLIANT.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△ OBSOLETE	27.79	20.32	15	24.89	34	△	6-104666-3
△ OBSOLETE	1.255	5.08	4	9.65	10	△	6-104666-2
△	1.094	1.200		1.380			
△	22.71	15.24	12	19.81	26	△	6-104666-1
△	21.44	13.97	11	18.54	24	△	6-104666-0
△	16.36	8.89	7	13.46	16	△	5-104666-9
△	6.44	3.50		5.30			
△ OBSOLETE	49.38	46.99	33	46.48	68	△	6-104666-8
△	1.944	1.850		1.830			
△ OBSOLETE	44.30	36.83	29	41.40	60	△	5-104666-7
△	1.744	1.450		1.630			
△ OBSOLETE	69.70	62.23	49	66.80	100	△	6-104666-6
△	2.744	2.450		2.630			
△	57.00	49.53	39	54.10	80	△	5-104666-5
△	2.244	1.950		2.130			
△	37.95	30.48	24	35.05	50	△	5-104666-4
△	1.494	1.200		1.380			
△	31.60	24.13	19	28.70	40	△	5-104666-3
△	1.244	0.950		1.130			
△	25.25	17.78	14	22.35	30	△	5-104666-2
△	9.94	7.00		8.80			
△	18.90	11.43	9	16.00	20	△	5-104666-1
△	7.44	4.50		6.30			
△	27.79	20.32	15	24.89	34	△	1-104666-3
△	1.094	1.200		1.380			
△	12.55	5.08	4	9.65	10	△	1-104666-2
△	1.494	1.200		1.380			
△	22.71	15.24	12	19.81	26	△	1-104666-1
△	21.44	13.97	11	18.54	24	△	1-104666-0
△	16.36	8.89	7	13.46	16	△	104666-9
△	6.44	3.50		5.30			
△ OBSOLETE	49.38	41.91	33	46.48	68	△	104666-8
△	1.944	1.850		1.830			
△	44.30	36.83	29	41.40	60	△	104666-7
△	1.744	1.450		1.630			
△	69.70	62.23	49	66.80	100	△	104666-6
△	2.744	2.450		2.630			
△	57.00	49.53	39	54.10	80	△	104666-5
△	2.244	1.950		2.130			
△	37.95	30.48	24	35.05	50	△	104666-4
△	1.494	1.200		1.380			
△	31.60	24.13	19	28.70	40	△	104666-3
△	1.244	0.950		1.130			
△	25.25	17.78	14	22.35	30	△	104666-2
△	9.94	7.00		8.80			
△	18.90	11.43	9	16.00	20	△	104666-1
△	7.44	4.50		6.30			
G	C	B	A				

NO OF POSN
PART NUMBER

TE Connectivity

HEADER ASSY, VERTICAL SHROUDED
DOUBLE ROW W/SIDE & END LATCHES
AMP/COU SYSTEM 50

114-25031

A1 00779 104666

SCALE 4:1