



THIS DRAWING IS UNPUBLISHED
 ALL RIGHTS RESERVED

REV	DATE	DESCRIPTION	BY	CHK	APP
00		REVISED PER EDD-11-013373			



- △ MATERIAL: CONNECTOR-NYLON UL94V-2 (BLUE).
 CONTACTS-0.30 [.012] THICK COPPER ALLOY
 0.00076 [.000030] GOLD OR 0.00076[.000030]
 TOTAL GOLD FLASH OVER PALLADIUM NICKEL,
 PER TE CONNECTIVITY'S DISCRETION, IN CONTACT
 AREA WITH BRIGHT TIN-LEAD FOR 641239-2 THRU
 2-641239-8, MATTE WHISKER MITIGATED TIN
 FOR 3-641239-2 THRU 5-641239-8 OVER
 NICKEL UNDERPLATE.
- CONTACTS ACCEPT 26 AWG WIRE WITH 1.52 [.060] MAX INSULATION DIAMETER.
 - CONTACTS MUST ACCEPT 0.64±0.03 [.025±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.
 - IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.
 - DIMENSIONS IN BRACKETS ARE IN INCHES.
 - HOUSING FEATURES ARE: CLOSED END WITH LOCKING RAMP.
 - OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINISI

DIM A	NO. OF POSN	ASSEMBLY
71.12 [2.800]	28	5-641239-8
66.04 [2.600]	27	5-641239-7
63.50 [2.500]	26	5-641239-6
63.50 [2.500]	25	5-641239-5
60.96 [2.400]	24	5-641239-4
58.42 [2.300]	23	5-641239-3
55.88 [2.200]	22	5-641239-2
53.34 [2.100]	21	5-641239-1
50.80 [2.000]	20	5-641239-0
48.26 [1.900]	19	4-641239-9
45.72 [1.800]	18	4-641239-8
43.18 [1.700]	17	4-641239-7
40.64 [1.600]	16	4-641239-6
38.10 [1.500]	15	4-641239-5
35.56 [1.400]	14	4-641239-4
33.02 [1.300]	13	4-641239-3
30.48 [1.200]	12	4-641239-2
27.94 [1.100]	11	4-641239-1
25.40 [1.000]	10	4-641239-0
22.86 [.900]	9	3-641239-9
20.32 [.800]	8	3-641239-8
17.78 [.700]	7	3-641239-7
15.24 [.600]	6	3-641239-6
12.70 [.500]	5	3-641239-5
10.16 [.400]	4	3-641239-4
7.62 [.300]	3	3-641239-3
5.08 [.200]	2	3-641239-2

STANDARD LEAD

△ SUPERCEDED BY 5-641239-8
 △ SUPERCEDED BY 5-641239-7
 △ SUPERCEDED BY 5-641239-6
 △ SUPERCEDED BY 5-641239-5
 △ SUPERCEDED BY 5-641239-4
 △ SUPERCEDED BY 5-641239-3
 △ SUPERCEDED BY 5-641239-2
 △ SUPERCEDED BY 5-641239-1
 △ SUPERCEDED BY 5-641239-0
 △ SUPERCEDED BY 4-641239-9
 △ SUPERCEDED BY 4-641239-8
 △ SUPERCEDED BY 4-641239-7
 △ SUPERCEDED BY 4-641239-6
 △ SUPERCEDED BY 4-641239-5
 △ SUPERCEDED BY 4-641239-4
 △ SUPERCEDED BY 4-641239-3
 △ SUPERCEDED BY 4-641239-2
 △ SUPERCEDED BY 4-641239-1
 △ SUPERCEDED BY 4-641239-0
 △ SUPERCEDED BY 3-641239-9
 △ SUPERCEDED BY 3-641239-8

DIM A	NO. OF POSN	ASSEMBLY
71.12 [2.800]	28	2-641239-8
66.04 [2.600]	27	2-641239-7
63.50 [2.500]	26	2-641239-6
63.50 [2.500]	25	2-641239-5
60.96 [2.400]	24	2-641239-4
58.42 [2.300]	23	2-641239-3
55.88 [2.200]	22	2-641239-2
53.34 [2.100]	21	2-641239-1
50.80 [2.000]	20	2-641239-0
48.26 [1.900]	19	1-641239-9
45.72 [1.800]	18	1-641239-8
43.18 [1.700]	17	1-641239-7
40.64 [1.600]	16	1-641239-6
38.10 [1.500]	15	1-641239-5
35.56 [1.400]	14	1-641239-4
33.02 [1.300]	13	1-641239-3
30.48 [1.200]	12	1-641239-2
27.94 [1.100]	11	1-641239-1
25.40 [1.000]	10	1-641239-0
22.86 [.900]	9	641239-9
20.32 [.800]	8	641239-8
17.78 [.700]	7	641239-7
15.24 [.600]	6	641239-6
12.70 [.500]	5	641239-5
10.16 [.400]	4	641239-4
7.62 [.300]	3	641239-3
5.08 [.200]	2	641239-2

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT. (REV) (DATE)

TE CONNECTIVITY
 MTA .100 CONNECTOR ASSEMBLY
 26 AWG, STANDARD

108-1050
 114-1019

DATE: 00779
 SIZE: S:1