



RECOMMENDED MOUNTING HOLE PATTERN
 FOR .063 THICK P.C. BOARD

- △ POST TO WITHSTAND 13 NEWTONS (3 LBS) MIN. AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- △ TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- △ MEASURED AT SURFACE
- △ PLASTIC FLASH PERMITTED IN THIS AREA.
- 5. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- △ ONE HOLE MAY BE UNDERSIZED (.032-.035 DIA) FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- △ MATERIAL: HEADER-THERMOPLASTIC POLYESTER UL94V-0(NATURAL) POST-COPPER ALLOY (TIN-PLATED)
- △ COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9. PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- △ POSTS TO BE MEASURED WHEN STRIP IS HELD FLAT.
- △ POSTS MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- △ DIMENSION SHOULD BE .130 MIN WHEN MATING WITH A MTA 100 CONNECTOR ASSEMBLY OR A CST 100 CONNECTOR.
- △ PIN BURR OF .005 MAX. VERTICAL AND .003 MAX. HORIZONTAL PERMITTED AT POST TIPS ON BOTH ENDS.

	IN	MM	IN	MM
.040	1.02	1.000	25.40	
.035	0.89	.535	13.59	
.032	0.81	.310	7.87	
.025	0.64	.295	7.49	
.020	0.51	.225	5.72	
.015	0.38	.200	5.08	
.010	0.25	.140	3.56	
.008	0.20	.130	3.30	
.005	0.13	.125	3.18	
.003	0.08	.100	2.54	
.001	0.03	.063	1.60	
.000	0.00	.050	1.27	
IN	MM	IN	MM	

2	643879-6
6	643879-7
4 & 7	643879-6
5	643879-5
3	643879-4

643879-1 SHOWN	
OBSOLETE	
POST NUMBER OMITTED	PART NUMBER
B	643879-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNED BY	DATE	REVISED BY	DATE
DRAWN BY	DATE	REVISED BY	DATE
CHECKED BY	DATE	REVISED BY	DATE
APPROVED BY	DATE	REVISED BY	DATE

TE Connectivity
 MTA-100 HEADER ASSEMBLY, FRICTION LOCK, NOTCHED, .025 SQUARE STRAIGHT POST, TIN PLATED.

SIZE: 8.1
 DATE: 8.1
 REV: 1
 G1

