



- △ MATERIAL:
RECEPTACLE CONTACTS— PHOSPHOR BRONZE
RECEPTACLE HOUSING AND TERMINATING COVERS— THERMOPLASTIC,
COLOR: BLACK.
- △ PLATING:
RECEPTACLE CONTACTS— 0.00076 [0.00030] MINIMUM GOLD PLATE IN CONTACT AREA,
0.00127 [0.00050] MINIMUM BRIGHT TIN-LEAD PLATE IN TERMINATION AREA,
ALL OVER 0.00127 [0.00050] MINIMUM NICKEL.
- 3 RECOMMENDED WIRE:
28 AWG— 0.91 [0.36] MAX O.D. PVC OR POLYETHYLENE INSULATION.
- 4 SHORT—LONG CONTACT SEQUENCE MUST ALTERNATE BUT MAY BEGIN WITH EITHER
A SHORT OR LONG CONTACT.
- △ PLATING:
RECEPTACLE CONTACTS— 0.00076 [0.00030] MINIMUM GOLD PLATE IN CONTACT AREA,
0.00127 [0.00050] MINIMUM MATTE TIN PLATE IN TERMINATION AREA,
ALL OVER 0.00127 [0.00050] MINIMUM NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

NO.	REV.	DATE	DESCRIPTION	BY	CHK	APP	
OBSOLETE	△	71.83	63.91	62.23	49	100	6-104892-0-
		2.828	2.516	2.450			
OBSOLETE	△	65.48	57.56	55.88	44	90	5-104892-9-
		2.578	2.266	2.200			
	△	59.13	51.21	49.53	39	80	5-104892-8
		2.328	2.016	1.950			
	△	52.78	44.86	43.18	34	70	5-104892-7
		2.078	1.766	1.700			
OBSOLETE	△	46.43	38.51	36.83	29	60	5-104892-6-
		1.828	1.516	1.450			
	△	40.08	32.16	30.48	24	50	5-104892-5
		1.578	1.266	1.200			
	△	33.73	25.81	24.13	19	40	5-104892-4
		1.328	1.016	0.950			
	△	27.38	19.46	17.78	14	30	5-104892-3
		1.078	0.766	0.700			
	△	21.03	13.11	11.43	9	20	5-104892-2
		0.828	0.516	0.450			
OBSOLETE	△	14.68	6.76	5.08	4	10	5-104892-1
		0.578	0.266	0.200			
OBSOLETE	△	71.83	63.91	62.23	49	100	1-104892-0-
		2.828	2.516	2.450			
OBSOLETE	△	65.48	57.56	55.88	44	90	104892-9
		2.578	2.266	2.200			
	△	59.13	51.21	49.53	39	80	104892-8
		2.328	2.016	1.950			
	△	52.78	44.86	43.18	34	70	104892-7
		2.078	1.766	1.700			
OBSOLETE	△	46.43	38.51	36.83	29	60	104892-6-
		1.828	1.516	1.450			
	△	40.08	32.16	30.48	24	50	104892-5
		1.578	1.266	1.200			
	△	33.73	25.81	24.13	19	40	104892-4
		1.328	1.016	0.950			
	△	27.38	19.46	17.78	14	30	104892-3
		1.078	0.766	0.700			
	△	21.03	13.11	11.43	9	20	104892-2
		0.828	0.516	0.450			
OBSOLETE	△	14.68	6.76	5.08	4	10	104892-1
		0.578	0.266	0.200			

THIS DRAWING IS A CONTROLLED DOCUMENT. (REV. 00) (DATE 11-04-80)

TE Connectivity

UNLESS OTHERWISE SPECIFIED:	UNIT: INCHES	SCALE: AS SHOWN	DATE: 11-04-80
FINISH: AS SHOWN	TOLERANCES: FRACTIONS DECIMALS	PROJECT: AMPMODU	50/50 GRID CABLE CONN. ASSY
ASSEMBLY: 108-1443	OPERATION: 114-7010	SIZE: 10-11	DRAWING NO: 104892
REVISION: 00	DATE: 11-04-80	BY: AD	CHK: G1

CUSTOMER DRAWING