



RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57 [0.62] THICK P.C. BOARD

DETAIL C

VIEW A-A SCALE 16:1

1. MATERIAL HOUSING: THERMOPLASTIC POLYESTER, GLASS FILLED, UL94V-0 POST: COPPER ALLOY

2. FINISH HOUSING: NATURAL

3. UL MARKING MAY NOT APPEAR ON THE 2 OR 3 POSITION SIZES. CSA MARKING MAY NOT APPEAR ON THE 2 POSITION SIZE.

4. POST SOLDERTAILS COMPLY WITH TYCO SOLDERABILITY SPECIFICATION 109-11-2.

5. POST WITHSTANDS 13.34 NEWTONS (3 LBS) MINIMUM AXIAL FORCE IN EITHER DIRECTION WITHOUT DISLOGGING.

6. APPLIES AT [-A-]

7. APPLIES WHEN THE HEADER IS STRAIGHT.

8. PLASTIC PROJECTIONS PERMITTED IN THIS ZONE.

9. COORDINATE DIMENSIONS APPLIES FROM CENTER OF THE ACTUAL FEATURE.

10. SOLDER SIDE OF BOARD IS SHOWN.

11. THE RETENTION TABS PROVIDE A ONE-TIME INTERFERENCE FIT IN THE 1.63 [0.64] DIAMETER BOARD HOLES FOR HEADER ASSEMBLY RETENTION DURING SOLDERING. FOUR TABS PER PEG, TWO PEGS PER HEADER ASSEMBLY (ONE PEG ONLY FOR 2 POSITION SIZE).

12. PLATING: GOLD PLATE AREA, 0.00076 [0.00030] GOLD OR 0.00008 [0.00003] MIN GOLD FLASH OVER 0.00068 [0.00027] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [0.00050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST

13. PLATING: BRIGHT TIN-LEAD (93/7) PLATE AREA, 0.00381-0.00889 [0.00150-0.00350] THICK, ALL FOUR SIDES, OVER, 3.18 [1.25] MINIMUM.

14. DIMENSIONS IN BRACKETS ARE IN INCHES.

15. ALL POSITION SIZES HAVE THE BACK WALL NOTCHED ON BOTH ENDS AS SHOWN. THE 2 THRU 5 POSITION SIZES HAVE SOLID BACK WALLS. POSITION SIZES 6 AND ABOVE HAVE AN INTERRUPTED BACK WALLS AT VARIOUS LOCATIONS (SEE TABLE FOR INTERRUPTION(S) LOCATIONS).

16. EDGE OF POLARIZING LOCK WALL TO BE IN LINE WITH CENTERLINE OF ADJACENT POST WITHIN ±0.13 [0.005].

17. PLATING: MATTE TIN PLATE AREA, 0.00381-0.00889 [0.00150-0.00350] THICK, ALL FOUR SIDES, OVER, 3.18 [1.25] MINIMUM.

4&5 7&8 11&12 14&15	71.20	[2.803]	18	4-644633-8
4&5 7&8 10&11 13&14	67.23	[2.647]	17	4-644633-7
4&5 8&9 12&13	63.27	[2.491]	16	4-644633-6
4&5 8&9 11&12	59.31	[2.335]	15	4-644633-5
4&5 7&8 10&11	55.35	[2.179]	14	4-644633-4
4&5 7&8 10&11	51.38	[2.023]	13	4-644633-3
4&5 8&9	47.42	[1.867]	12	4-644633-2
4&5 7&8	43.46	[1.711]	11	4-644633-1
3&4 7&8	39.50	[1.555]	10	4-644633-0
3&4 6&7	35.53	[1.399]	9	3-644633-9
4&5	31.57	[1.243]	8	3-644633-8
4&5	27.61	[1.087]	7	3-644633-7
3&4	23.65	[931]	6	3-644633-6
NONE	19.69	[775]	5	3-644633-5
NONE	15.72	[619]	4	3-644633-4
NONE	11.76	[463]	3	3-644633-3
NONE	7.80	[307]	2	3-644633-2

BACK WALL INTERRUPTIONS BETWEEN POSTS (L) NO OF POSN ASSEMBLY

THE ABOVE IS A COPYRIGHTED DOCUMENT. IT IS THE PROPERTY OF METRIC INC. IT IS TO BE USED ONLY FOR THE PURPOSES SPECIFIED IN THE ORIGINAL ORDER. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT THE WRITTEN PERMISSION OF METRIC INC. ALL RIGHTS ARE RESERVED.

DATE: 10/07/92

DESIGNER: CHANG

TE Connectivity

150-156 HEADER ASSEMBLY, POLARIZED LOCK, RIGHT WALL FROM BOARD AND SQUARE POST

400779-00-644633

1 1 P 1

