



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
- MATERIAL:  
 HOUSING & COVER - THERMOPLASTIC, BLACK.  
 TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
2. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
3. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
4. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
5. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
6. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS, TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
7. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-6076 & APPLICATION SPEC 114-6030.

REVISONS		DATE	BY
GP	00	17/8/83	BM1 W/M
H		17/8/83	BM1 W/M

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE		SCALE	
DIMENSIONS INCHES		16/06/07		2:1	
TOLERANCES UNLESS OTHERWISE SPECIFIED		Z. BEZAL		SHEET 1 OF 1	
FRACTIONS		16/06/07		REV H	
DECIMALS		16/06/07		AS SHOWN 553602-1	
ANGLES		16/06/07		DESCRIPTION PART NUMBER	
HOLE DIA		16/06/07		PUG ASSEMBLY, 50 POSITION	
HOLE DIA		16/06/07		SCREEN COCK, LOW PROFILE,	
HOLE DIA		16/06/07		SCREW COCK, LATCH	
HOLE DIA		16/06/07		RESERVED TO	
HOLE DIA		16/06/07		CUSTOMER DRAWING	
HOLE DIA		16/06/07		553602	