


THIS DRAWING IS UNCLASSIFIED  
 UNLESS INDICATED OTHERWISE  
 ALL RIGHTS RESERVED

REV	DATE	DESCRIPTION	BY	CHK	APP
00					
01		REVISED PER EDD-11-00503	K1		RK HMR

EJECTION LATCHES OMITTED IN THIS VIEW FOR CLARITY



- △ COORDINATE DIMENSION APPLIES FROM BASIC LOCATION.
- △ 10 AND 14 POSITION SIZES CONTAIN ONLY ONE SLOT FOR SNAP-IN POLARIZER (MILITARY POLARIZATION) LOCATED AS SHOWN.
- △ 10 POSITION SIZES CONTAIN ONLY ONE SLOT FOR DUAL POLARIZATION, LOCATED AS SHOWN.
- 4. RECOMMENDED PRINTED CIRCUIT BOARD THICKNESS IS 3.18 [1.25].
- △ DISTANCE REQUIRED BY EJECTION LATCHES IN THE OPEN POSITION.
- △ POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.76µm[.000030] MIN TOTAL ON THE LOCALIZED PLATE AREA, 2.54µm[.000100] MIN TIN-LEAD PLATE ON THE SOLDER-TAIL, 1.27µm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST. -08
- △ 0.76µm[.000030] MIN GOLD PLATE ON THE LOCALIZED PLATE AREA, 2.54µm[.000100] MIN TIN-LEAD PLATE ON THE SOLDER-TAIL, 1.27µm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.

	53.34	71.12	65.02	75.18	71.12	60.96		
OBsolete	2.100	2.800	2.560	2.960	2.800	2.400	44	1-102321-3
	78.74	96.52	90.42	100.58	96.52	86.36	64	1-102321-2
	3.100	3.800	3.560	3.960	3.800	3.400		
	73.66	91.44	85.34	95.50	91.44	81.28	60	1-102321-1
	2.900	3.600	3.360	3.760	3.600	3.200		
	60.96	78.74	72.64	82.80	78.74	68.58	50	1-102321-0
	2.400	3.100	2.860	3.260	3.100	2.700		
	48.26	66.04	59.94	70.10	66.04	55.88	40	102321-9
	1.900	2.600	2.360	2.760	2.600	2.200		
	40.64	58.42	52.32	62.48	58.42	48.26	34	102321-8
	1.600	2.300	2.060	2.460	2.300	1.900		
	35.56	53.34	47.24	57.40	53.34	43.18	30	102321-7
	1.400	2.100	1.860	2.260	2.100	1.700		
	30.48	48.26	42.16	52.32	48.26	38.10	26	102321-6
	1.200	1.900	1.660	2.060	1.900	1.500		
OBsolete	27.94	45.72	39.62	49.78	45.72	35.56	24	102321-5
	1.100	1.800	1.560	1.960	1.800	1.400		
	22.86	40.64	34.54	44.70	40.64	30.48	20	102321-4
	1.900	1.600	1.360	1.760	1.600	1.200		
	17.78	35.56	29.46	39.62	35.56	25.40	16	102321-3
	1.700	1.400	1.160	1.560	1.400	1.000		
	15.24	33.02	26.92	37.08	33.02	22.86	14	102321-2
	1.600	1.300	1.060	1.460	1.300	1.900		
	10.16	27.94	21.84	32.00	27.94	17.78	10	102321-1
	1.400	1.100	1.860	1.260	1.100	1.700		

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV	DATE	DESCRIPTION	BY	CHK	APP
REV	DATE	DESCRIPTION	BY	CHK	APP		
00							
01		REVISED PER EDD-11-00503	K1		RK HMR		

TE Connectivity  
 HEADER ASSY, UNIVERSAL AMP-LATCH  
 108-40018  
 DATE: 11-28-98  
 REV: 0000  
 PART NUMBER: 108-40018  
 CUSTOMER DRAWING: A100779  
 SCALE: 4:1  
 SHEET: 1 of 1  
 K1