



- △ COORDINATE DIMENSION APPLIES FROM BASIC LOCATION.
- △ 10 AND 14 POSITION SIZES CONTAIN ONLY ONE SLOT FOR SNAP-IN POLARIZER (MILITARY POLARIZATION) LOCATED AS SHOWN.
- △ 10 POSITION SIZES CONTAIN ONLY ONE SLOT FOR DUAL POLARIZATION, LOCATED AS SHOWN.
- 4. RECOMMENDED PRINTED CIRCUIT BOARD THICKNESS IS 3.18 [125].
- △ DISTANCE REQUIRED BY EJECTION LATCHES IN THE OPEN POSITION.
- △ POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.76µm[000030] MIN TOTAL ON THE LOCALIZED PLATE AREA, 2.54µm[000100] MIN TIN-LEAD PLATE ON THE SOLDER TAIL, 1.27µm[000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
 -OR-
 0.76µm[000030] MIN GOLD PLATE ON THE LOCALIZED PLATE AREA, 2.54µm[000100] MIN TIN-LEAD PLATE ON THE SOLDER TAIL, 1.27µm[000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.

	53.34	71.12	65.02	75.18	71.12	60.96	44	1-499374-3
OBSOLETE	2.100	2.800	2.560	2.960	2.800	2.400		
OBSOLETE	78.74	96.52	90.42	100.58	96.52	86.36	64	1-499374-2
OBSOLETE	73.66	91.44	85.34	95.50	91.44	81.28	60	1-499374-1
OBSOLETE	2.900	3.600	3.360	3.760	3.600	3.200		
OBSOLETE	60.96	78.74	72.64	82.80	78.74	68.58	50	1-499374-0
OBSOLETE	2.400	3.100	2.860	3.260	3.100	2.700		
OBSOLETE	48.26	66.04	59.94	70.10	66.04	55.88	40	499374-9
OBSOLETE	1.900	2.600	2.360	2.760	2.600	2.200		
OBSOLETE	40.64	58.42	52.32	62.48	58.42	48.26	34	499374-8
OBSOLETE	1.600	2.300	2.060	2.460	2.300	1.900		
OBSOLETE	35.56	53.34	47.24	57.40	53.34	43.18	30	499374-7
OBSOLETE	1.400	2.100	1.860	2.260	2.100	1.700		
OBSOLETE	30.48	48.26	42.16	52.32	48.26	38.10	26	499374-6
OBSOLETE	1.200	1.900	1.660	2.060	1.900	1.500		
OBSOLETE	27.94	45.72	39.62	49.78	45.72	35.56	24	499374-5
OBSOLETE	1.100	1.800	1.560	1.960	1.800	1.400		
OBSOLETE	22.86	40.64	34.54	44.70	40.64	30.48	20	499374-4
OBSOLETE	0.900	1.600	1.360	1.760	1.600	1.200		
OBSOLETE	17.78	35.56	29.46	39.62	35.56	25.40	16	499374-3
OBSOLETE	0.700	1.400	1.160	1.560	1.400	1.000		
OBSOLETE	15.24	33.02	26.92	37.08	33.02	22.86	14	499374-2
OBSOLETE	10.16	27.94	21.84	32.00	27.94	17.78	10	499374-1
OBSOLETE	0.400	1.100	0.860	1.260	1.100	0.700		

F	E	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV. 00	DATE 11-30-99	TDS Electronics Corporation	
DRAWN BY: [Signature]		DATE: 11-30-99	REV: 0000	Harrisburg, PA 17105-3608	
CHECKED BY: [Signature]		DATE: 11-30-99	REV: 0000	108-40018	
APPROVED BY: [Signature]		DATE: 11-30-99	REV: 0000	HEADERS ASSY, UNIVERSAL	
TITLE: 108-40018		DATE: 11-30-99	REV: 0000	AMP-LATCH	
PART NUMBER: 108-40018		DATE: 11-30-99	REV: 0000	DRAWN BY: [Signature]	
CUSTOMER DRAWING		DATE: 11-30-99	REV: 0000	CHECKED BY: [Signature]	