



NOTES:

- PACKING-DON'T NEED INSTALL COVER ON LOWER BOX. ENCLOSE LOOSELY.
- FUNCTION OF DIODE: BLOCKING DIODE.
- POTTING NEEDED PRIOR TO FIELD INSTALLATION. FOR MORE DETAILED INSTRUCTION, REFER TO APPLICATION SPEC 114-106008.

CURRENT RATING	BA	25A	25A			
	1	1	1	STUDER, 4.0MM2, UL/TUV	CABLE	7
	1	-	-		BLOCKING DIODE	6
	-	1	-		SOLARLOK SOCKET CONNECTOR	5
	1	-	1		SOLARLOK PIN CONNECTOR	4
	2	1	1	COPPER ALLOY	CONTACT RAIL	3
	1	1	1	PA66	BASE HOUSING	2
	1	1	1	PPD	COVER	1
	-3	-2	-1	MATERIAL/TYPE	DESCRIPTION	ITEM No.

QTY PER ASSY

QTY	DESCRIPTION	ITEM No.
1	STUDER, 4.0MM2, UL/TUV	7
1	BLOCKING DIODE	6
1	SOLARLOK SOCKET CONNECTOR	5
1	SOLARLOK PIN CONNECTOR	4
2	COPPER ALLOY	3
1	PA66	2
1	PPD	1

THIS DRAWING IS A CONTROLLED DOCUMENT. OWN: ALEX ZHANG, DATE: NOV2010, CBY: ROJAY CHEN, APPRO: JULIAN ZHOU, PRODUCT SPEC: 108-106055, APPLICATION SPEC: 114-106008, WEIGHT: -, MATERIAL: -, FINISH: -. CUSTOMER DRAWING.

TE Connectivity

ASSEMBLY, 1 RAIL JUNCTION BOX WITH CONN.

SHEET CASE CODE DRAWING NO. RESTRICTED TO: A2 - ©-1971645

SCALE: 1:1 SHEET 1 OF 1 REV: A2