THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -.-.-
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
H	–

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	ECO-12-003005	22FEB2012	SY	MQW











5100145

NOTES:

1. MATERIAL CONTACT; PHOSPHORBRONZE
   MATERIAL HOUSING; GLASSFILLED POLYESTER (GRAY)
   UL–RATING 94VO.
2. GENERAL PLATING SPECIFICATION: UNDERPLATING (ENTIRE CONTACT): 1,27µm NICKEL MIN. AND ACTION PIN: 0,5µm TIN MIN.
   FOR PLATING OF MATING SURFACES SEE APPLICABLE SPECIFICATION REFERENCE FOR EACH DASH NUMBER.
3. CONFORMS TO ALL TESTING ACCORDING IEC 61076–4–101 PERFORMANCE LEVEL 2.
4. CONFORMS TO ALL TESTING ACCORDING IEC 61076–4–101 PERFORMANCE LEVEL 1.
5. CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR–1217–CORE QUALITY LEVEL III, CENTRAL OFFICE APPLICATIONS.
6. CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR–1217–CORE QUALITY LEVEL III, UNCONTROLLED ENVIRONMENT APPLICATIONS.
7. CONNECTOR LUBRICATED WITH TELCORDIA GR–1217–CORE APPROVED LUBRICANT.
8. CONNECTOR PRINTED WITH PARTNUMBER AND DATECODE
   THE MARKING CAN APPEAR ON THE FRONT SIDE OR ON THE BACK SIDE.
9. PLATED–THROUGH HOLES AT 2x2mm SQUARE GRID. 125 HOLES
10. FITS WITH INTEGRATED GROUND RETURN UPPERSHIELD, BASIC P.N. 5338109 AND INTEGRATED GROUND RETURN LOWERSHIELD, BASIC P.N. 5338110
11. CONNECTOR ASSEMBLED WITH REDESIGNED CONTACTS.
12. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
13. 0.76µm MIN. GOLD PLATING AT MATING SURFACES.



SCALE 2,5:1
COMPONENT SIDE AS SHOWN
RECOMMENDED PCB–HOLE LAY–OUT

P.C.B. HOLE DIM. ACTION PIN
FOR DETAILS SEE
APPLICATION SPECIFICATION

1,2,3,11	1	3–5100145–0 11
2,6,7	1	12 1–5100145–9 11
2,5,7	1	5100145–9 11
2,4	1	12 5100145–4 11
2,5	1	5100145–1 11
FINISH	MATERIAL	PARTNUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm
TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± ±0.2
3 PLC ± –
4 PLC ± –
ANGLES ±
MATERIAL –
FINISH –

DWN	05AUG2004	K.N.KIRAN
CHK	22SEP2004	B.MOOIJ
APVD	22SEP2004	B.MOOIJ
PRODUCT SPEC		108–19082
APPLICATION SPEC		114–19029
WEIGHT		–

TE Connectivity

NAME
Z–PACK 2mm HM TYPE B
125 POS. FEMALE CONNECTOR
–

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C–5100145	–

CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1	REV E

1471–9 (3/11)

Downloaded from Elcodis.com electronic components distributor