



- △ CONTACTS DESIGNED FOR 26 & 28 AWG STRANDED OR 26, 28, & 30 AWG SOLID WIRE.
- △ AMP TRADEMARK LOCATED IN APPROX AREA SHOWN.
- △ STANDOFFS: POS 10 (2) STANDOFFS AS SHOWN.  
 14-16 (3) STANDOFFS, (1) CENTERED BETWEEN (2) SHOWN  
 20-26 (4) (2)  
 30 (5) (3)  
 34 (6) (4)  
 40-44 (7) (5)  
 50 (8) (6)  
 60 (9) (7)  
 64 (10) (8)
- △ .000100-.000200 BRIGHT TIN LEAD, ALL OVER .000050 NICKEL.
- △ HEIGHT AFTER TERMINATION IS .253 REF.
- △ .000050 MIN GOLD ON RIBBON CABLE TERMINATION AREA  
 .000100-.000200 MIN MATTE TIN ON SOLDER TAILS, ALL OVER .000050 MIN NICKEL.
- △ MOLDED PARTS, 94V-0 RATED THERMOPLASTIC, COLOR: BLACK. CONTACTS: PHOS BRONZE.

△	2.100	21	2.380	2.100	2.150	43	44	2-746610-6
△	3.100	31	3.380	3.100	3.150	63	64	2-
△	2.900	29	3.180	2.900	2.950	59	60	2-
△	1.100	11	1.380	1.100	1.150	23	24	2-
△	.600	6	.880	.600	.650	13	14	2-
△	2.400	24	2.680	2.400	2.450	49	50	2-
△	1.900	19	2.180	1.900	1.950	39	40	1-
△	1.400	14	1.680	1.400	1.450	29	30	1-
△	1.200	12	1.480	1.200	1.250	25	26	1-
△	.900	9	1.180	.900	.950	19	20	1-
△	.700	7	.980	.700	.750	15	16	1-
OBSOLETE	2.100	21	2.380	2.100	2.150	43	44	1-
OBSOLETE	3.100	31	3.380	3.100	3.150	63	64	1-
OBSOLETE	2.900	29	3.180	2.900	2.950	59	60	1-
OBSOLETE	2.400	24	2.680	2.400	2.450	49	50	1-
△	1.900	19	2.180	1.900	1.950	39	40	-9
△	1.600	16	1.880	1.600	1.650	33	34	-8
OBSOLETE	1.400	14	1.680	1.400	1.450	29	30	-7
△	1.200	12	1.480	1.200	1.250	25	26	-6
OBSOLETE	.900	9	1.180	.900	.950	19	20	-4
△	.700	7	.980	.700	.750	15	16	-3
△	.600	6	.880	.600	.650	13	14	-2
△	.400	4	.680	.400	.450	9	10	746610-1

CONTACT FINISH	F	E	D	C	B	A	NO OF POSH	PART NO
114-40005								

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 11-28-81  
 BY: M. WILMSLEY  
 KIT, AMP-LATCH DIP PLUG, PREASSEMBLED, .100 x .100 CENTERS.  
 114-40005  
 108-40013  
 114-40005  
 100779  
 746610