



- ⚠ FOR MINI-APPLICATOR AND STRIPPER CRIMPER.
- ⚠ FOR HAND TOOL USE ONLY.
- 3. WIRE RANGE OF 24-28, INSULATION RANGE OF .030-.040.
- 4. TIN PLATING MAY NOT APPEAR ON CARRIER STRIP.
- ⚠ GOLD FLASH IN LOCALIZED GOLD PLATE AREA, 2.54μm [.000100] MIN TIN ON WIRE BARRELS, ALL OVER 0.76μm [.000030] MIN NICKEL UNDERPLATE.
- ⚠ GOLD FLASH IN LOCALIZED GOLD PLATED AREA, 0.76μm [.000030] MIN TIN ON WIRE BARRELS, ALL OVER 0.76μm [.000030] MIN NICKEL UNDERPLATE.
- ⚠ GOLD PLATED IN LOCALIZED GOLD PLATE AREA AS FOLLOWS:
 0.76μm [.000030] MIN GOLD IN MATED AREA,
 2.54μm [.000100] MIN TIN ON WIRE BARRELS, ALL OVER
 1.27μm [.000050] MIN NICKEL UNDERPLATE.
 OR
 GOLD FLASH OVER
 PALLADIUM-NICKEL PLATE, 0.76μm [.000030] MIN TOTAL IN MATED AREA,
 2.54μm [.000100] MIN TIN ON WIRE BARRELS, ALL OVER
 1.27μm [.000050] MIN NICKEL UNDERPLATE.
- ⚠ FOR STANDARD APPLICATOR ONLY.

FINISH	USE	TYPE	PART NUMBER
⚠	⚠	STRIP	1658540-6
⚠	⚠	LOOSE PIECE	1658540-5
⚠	⚠	STRIP	1658540-4
⚠	⚠	STRIP	1658540-3
⚠	⚠	LOOSE PIECE	1658540-2
⚠	⚠	STRIP	1658540-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		M. JARRELA 11-19-04 M. BOLASH 11-19-04 M. WILMSLEY 11-19-04 108-40005 114-10000 CUSTOMER DRAWING	TE Connectivity PIN CONTACT, 20 DF, 24-28 AWG, AMPLIMITE	SIZE: 10-1 SHEET: 1 OF 1 DT
--	--	---	--	-----------------------------------