



REV	APP	DATE	DESCRIPTION	DESIGNER	DRAWN	INSP
AD	39			L3	11M11	RK

- 0.00076[.000030] GOLD AT POINT OF MEASUREMENT, 0.0005[.000020] MIN AT THE END POINTS OF AREA G, (LOCALIZED GOLD PLATE AREA), 0.0038[.000150] TIN-LEAD ON LOCALIZED TIN PLATED AREA, ALL OVER 0.0013[.000050] NICKEL.
- USE 1.32±0.02 [1.052±.001] DRILLED HOLE (#55 DRILL), FINISH TO BE TIN OVER 0.02 [0.001] MIN COPPER.
- DIMENSION APPLIES AT BASE OF SHROUD.
- THE NOTED DIMENSIONS APPLY AT THE MATING FACE OF THE HOUSING.
- 0.0038 [0.000150] TIN-LEAD ON HOLD DOWNALL OVER 0.0013 [0.000050] NICKEL.
- 6. IF PLANNING TO USE MORE THAN ONE MATING PAIR OF CONNECTORS TO INTERCONNECT 2 BOARDS, PLEASE REFER TO THE SPACING PARAGRAPH IN APPLICATION SPEC, #114-7010
- POINT OF MEASUREMENT
- DIMENSIONS NOTED APPLY FROM THE BASIC DIMENSION LINE (NOT THE CIRCUIT CAVITY CENTER LINE) TO THE SURFACE INDICATED.
- 0.00076[.000030] GOLD AT POINT OF MEASUREMENT, 0.0005[.000020] MIN AT THE END POINTS OF AREA G, (LOCALIZED GOLD PLATE AREA), 0.0038[.000150] TIN ON LOCALIZED TIN PLATED AREA, ALL OVER 0.0013[.000050] NICKEL.
- 0.0035[.000150] TIN ON HOLDDOWN, ALL OVER 0.0013[.000050] NICKEL
- ROHS 2002/95/EC COMPLIANT.
- OBSELETE PARTS: OBSELETE CIS STREAMLINED PER D.RENAUD/D.SINISI

OBSELETE

OBSELETE

OBSELETE

OBSELETE

65.33	32.66	66.59	64.05	49	100	△	6-104655-1
58.97	29.48	60.24	57.70	44	90	△	6-104655-0
52.63	26.31	53.89	51.35	39	80	△	5-104655-9
46.28	23.13	47.54	45.00	34	70	△	5-104655-8
39.93	19.96	41.19	38.65	29	60	△	5-104655-7
33.58	16.78	34.84	32.30	24	50	△	5-104655-6
27.23	13.61	28.49	25.95	19	40	△	5-104655-5
20.88	10.43	22.14	19.60	14	30	△	5-104655-4
14.53	7.26	15.79	13.25	9	20	△	5-104655-3
11.98	5.99	13.25	10.72	7	16	△	5-104655-2
8.18	4.08	9.44	6.90	4	10	△	5-104655-1
65.33	32.66	66.59	64.05	49	100	△	1-104655-1
58.97	29.48	60.24	57.70	44	90	△	4-104655-0
52.63	26.31	53.89	51.35	39	80	△	104655-9
46.28	23.13	47.54	45.00	34	70	△	104655-8
39.93	19.96	41.19	38.65	29	60	△	104655-7
33.58	16.78	34.84	32.30	24	50	△	104655-6
27.23	13.61	28.49	25.95	19	40	△	104655-5
20.88	10.43	22.14	19.60	14	30	△	104655-4
14.53	7.26	15.79	13.25	9	20	△	104655-3
11.98	5.99	13.25	10.72	7	16	△	404655-2
8.18	4.08	9.44	6.90	4	10	△	104655-1

THIS DRAWING IS A CONTROLLED DOCUMENT. THE HELM (REV) IT. (REV) DATE

INCHES	REVISED BY	DATE
MM	BY	
	DATE	

DATE: 114-7010
CUST: 100779
REV: 10-1