



REV	DATE	DESCRIPTION	BY	CHK
AD	00	REVISED PER EDD-11-04587	11MMR11	RK HMR

- △ 0.00076[.000030] GOLD AT POINT OF MEASUREMENT, 0.00051[.000020] MIN AT THE END POINTS OF AREA G, (LOCALIZED GOLD PLATE AREA), 0.0038[.000150] TIN-LEAD ON LOCALIZED TIN PLATED AREA, ALL OVER 0.0013[.000050] NICKEL
- △ USE 1.32±0.02[.0520±.0010] DRILLED HOLE (#55 DRILL), FINISH TO BE TIN-LEAD OVER 0.02[.001] MIN COPPER.
- △ DIMENSION APPLIES AT BASE OF SHROUD.
- △ THE NOTED DIMENSIONS APPLY AT THE MATING FACE OF THE HOUSING.
- △ 0.0038[.000150] TIN-LEAD ON HOLD DOWN, ALL OVER 0.0013[.000050] NICKEL.
- 6. IF PLANNING TO USE MORE THAN ONE MATING PAIR OF CONNECTORS TO INTERCONNECT 2 BOARDS, PLEASE REFER TO SPACING PARAGRAPH IN APPLICATION SPEC, #114-7010
- △ POINT OF MEASUREMENT
- △ DIMENSIONS NOTED APPLY FROM THE BASIC DIMENSION LINE (NOT THE CIRCUIT CAVITY CENTER LINE) TO THE SURFACE INDICATED.
- △ 0.00076[.000030] GOLD AT POINT OF MEASUREMENT, 0.00051[.000020] MIN AT THE END POINTS OF AREA G (LOCALIZED GOLD PLATE AREA), 0.0038[.000150] TIN ON LOCALIZED TIN PLATED AREA, ALL OVER 0.0013[.000050] NICKEL.
- △ USE 1.32±0.02[.0520±.0010] DRILLED HOLE (#55 DRILL) FINISH TO BE TIN OVER 0.02[.001] MIN COPPER.
- △ 0.0038[.000150] TIN ON HOLDDOWN, ALL OVER 0.0013[.000050] NICKEL
- △ ROHS 2002/95/EC COMPLIANT.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	BY	CHK
DATE	BY	DATE	BY	CHK
114-7010	A1	108-1332		
CUSTOMER DRAWING		DATE	BY	CHK
		10-1		