


REVISIONS				DATE	APPD
P	REVISED PER	ECR-08-032448	190808	S.Y.	
P1	REVISED PER	ECO-10-000443	200810	AEG	

- △ HOUSING MATERIAL: LIQUID CRYSTAL POLYMER PER ASTM D5138 LCP000 G30A 32250.
- △ CONTACT MATERIAL: PHOSPHOR BRONZE.
- △ CONTACT FINISH: UNDERPLATE (ENTIRE CONTACT): 0.00127 MIN NICKEL. ON MATING SURFACES: CONFORMS TO ALL TESTING SPECIFIED FOR TELCORDIA UNCONTROLLED ENVIRONMENT. ON LEADS: 0.0006 MIN TIN-LEAD OVER UNDERPLATE. LUBRICATION (ENTIRE CONTACT): SURFACE CONDITIONER PER AMP SPEC 112-1002 AFTER PLATING.
- △ PART MARKING PER AMP INCORPORATED SPECIFICATION 115-9009, LOCATED APPROXIMATELY AS SHOWN.
- △ DIMENSION APPLIES WHEN SEATED ON PRINTED CIRCUIT BOARD.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



OBsolete	4.25	58.00	29	59.88	120	536514-6-
OBsolete	4.25	72.00	35	71.88	144	536514-5
	4.25	94.00	47	93.88	192	536514-4
	4.25	46.00	23	47.88	96	536514-3
	4.25	22.00	11	23.88	48	536514-2
	4.25	10.00	5	11.88	24	536514-1

DO NOT SCALE PRINT. UNLESS SPECIFIED. DIMENSIONS IN MILLIMETERS TO NEAREST 0.1. 2 PLG DEC # 013. UNLESS # -.		DR 04/01/93 DLS/BER	Yao Electronics Corporation Shanghai, P.R.China, 200233	
MATERIAL		APPD 04/02/93 D/IMP/TNCK	NAME PIN ASSEMBLY, SIGNAL MODULE, Z-PACK 2mm FB 2mm, 4 ROW, 5.00mm MATING LENGTH PRESS FIT LEAD	
FINISH	APPLICATION SPEC	SIZE	CAGE CODE	DRAWING NO.
△ -	-	D	00779	536514
WEIGHT		SCALE 4:1		SHEET 10F 1

