



NUMBER 316081  
3RD ANGLE PROJECTION

METRIC

DIMENSIONS IN MILLIMETERS. DO NOT SCALE PRINT

PRINT DIST

**NOTES**

1. MATERIAL: HOUSING: GLASS FILLED THERMO PLASTIC, POLYESTER (94V-0), COLOR: BLACK  
CONTACT: COPPER ALLOY  
RETENTION LEG: COPPER ALLOY

△ FINISH (CONTACT AREA): 0.38 μm MIN GOLD PLATING OVER Ni PLATING  
 △ FINISH (CONTACT AREA): 0.76 μm MIN GOLD PLATING OVER Ni PLATING  
 △ FINISH (CONTACT AREA): 2.0 μm MIN TIN PLATED OVER NICKEL  
 △ FINISH (RETENTION LEG): TIN LEAD PLATED (CONTACT TAIL) OVER NICKEL  
 △ FINISH (RETENTION LEG): TIN PLATED (CONTACT TAIL) OVER NICKEL  
 △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

**注 記**

1. 材料: ハウジング: ガラス入り熱可塑性ポリエチレン樹脂 (94V-0), 色: 黒  
 コントクト: 銅合金  
 リテンションレグ: 銅合金

△ めっき: コントクト: 全面Ni下地  
 接触部: 0.38 μm MIN金めっき

△ めっき: コントクト: 全面Ni下地  
 接触部: 0.76 μm MIN金めっき

△ めっき: コントクト: 全面Ni下地  
 接触部: 2.0 μm MINスズめっき

△ めっき: リテンションレグとコンタクト半田付部  
 ニッケル下地の下に半田めっき

KEYING LOCATION	A ROW KEYING	B ROW KEYING	FINISH	製品番号	PART NO.
	X	Y	△△	3-316001-5	△
			△△	3-316081-3	
			△△	3-316081-2	
	Y	Y	△△	2-316081-5	
			△△	2-316081-3	
			△△	2-316081-2	
	X	X	△△	1-316081-5	
			△△	1-316081-3	
			△△	1-316081-2	

WIRE RANGE		INSULATION DIA		NAME	
mm²(AWG)		mm		12 POS DOUBLE ROW HORIZONTAL HDR ASS'Y FOR DYNAMIC D-3200	
MATERIAL SEE NOTE 注記参照		FINISH SEE NOTE 注記参照		(GENERAL TOLERANCE) 100% ±0.3 LONGER PART ±0.4 SHORTER PART ±0.45 * 23°	
DR: K.IKEDA CHK: Y.ISHIKAWA		DE: K.IKEDA APP: S.MANABE		SIZE A3	LOC J
REVISED PER ECO-11-005030		REVISION RECORD		NUMBER C-316081	SCALE 2-1
B4	REVISED PER ECO-11-005030	RK	HMR	REV. B4	SHEET 1 OF 1

(CUSTOMER DRAWING) 顧客用図面