



- △ CAVITY IDENTIFICATION CHARACTERS ON FRONT AND REAR FACE.
- △ RECEPTACLE: NYLON, UL 94V-0 RATED, BLACK; CONTACT AND POST: BRASS; SPRING: STAINLESS STEEL.
- △ SOCKET CONTACT AND POST: 2.54µm [.000100] MIN TIN-LEAD OVER 1.27µm [.000050] MIN NICKEL.
- △ SOCKET CONTACT AND POST: 2.54µm [.000100] MIN TIN OVER 1.27µm [.000050] MIN NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△ OBSOLETE	△	B, C, D, E, F, H, I, J, L, M, N	1-213928-4
	△	A, B, C, D, E, F, G, H, K	1-213928-3
	△	A, B, C, D, E, K	1-213928-2
	△	ALL	1-213928-1
△ OBSOLETE	△	B, C, D, E, F, H, I, J, L, M, N	213928-4
	△	A, B, C, D, E, F, G, H, K	213928-3
	△	A, B, C, D, E, K	213928-2
	△	ALL	213928-1
		FINISH	POSITIONS LOADED
			PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. PREPARED BY: J. G. STONE, 1 NOV 87. CHECKED BY: J. G. STONE, 1 NOV 87. DATE: 1 NOV 87. REVISIONS: 1. REVISIONS: 1. REVISIONS: 1.

TE Connectivity
RECEPTACLE ASSEMBLY, 20-14, REVERSE SEX, CPC

SIZE: A1, DATE: 00779, DRAWING NO: 213928, REVISED TO: C2