



- ▲ NYLON, UL 94V-0 RATED, RED.
- ▲ BRASS PER ASTM B36.
- ▲ 3.81um [.000150] MIN TIN OVER 2.54um [.000100] MIN COPPER.
- ▲ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] FROM MATING END, 3.81um [.000150] MIN TIN-LEAD FOR A LENGTH OF 4.83 [.190] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.
- ▲ .000150 MIN TIN OVER .000100 MIN CU, OR .000050 MIN NICKEL.
- ▲ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] FROM MATING END, 3.81um [.000150] MIN TIN FOR A LENGTH OF 4.83 [.190] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.

NO	1-207121-0
YES	207121-9
YES	207121-8
NO	207121-4
YES	207121-3
NO	207121-2
YES	207121-1

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 02/07/06. TYS ELECTRONICS CORPORATION, Harrisburg, Pa.

DESIGNER: J. J. ...	DATE: 3-17-02	REVISED: 3-17-02	BY: ...
HOLES: ...	108-10033	REVISED: ...	BY: ...
HOUSING: ...	DATE: ...	DATE: ...	DATE: ...

PIN HEADER ASSEMBLY, 36 POSITION, METRIMATE. CUSTOMER DRAWING: A100779 (Q)=207121. SHEET: 1 OF 1. DATE: Y1.