





- PARTS COMPLY TO AMP SOLDERABILITY SPECIFICATION 109-11-3.
- CONTACT IS PLATED OVERALL WITH 0.00127 [0.00050] NICKEL, THEN 0.00076 [0.00030] GOLD OVER CONTACT LENGTH INDICATED AND MATTE TIN LEAD ON SOLDER TAIL END.
- CIRCUIT IDENTIFICATION CHARACTERS ARE ADJACENT TO THE INDICATED CAVITIES, BUT LOCATION AND ORIENTATION MAY DIFFER FROM PRINT.
- DIMENSIONS IN BRACKETS ARE IN INCHES.
- CONTACT IS PLATED OVERALL WITH 0.00127 [0.00050] NICKEL, THEN 0.00076 [0.00030] GOLD OVER CONTACT LENGTH INDICATED AND MATTE TIN ON SOLDER TAIL END.



3-DIMENSIONAL MODEL NTS



RECOMMENDED MOUNTING HOLE PATTERN FOR 3.18 [.125] THICK P.C. BOARD

PHOSPHOR BRONZE, GOLD	NYLON,UL94V-0,WHITE	350787-3
PHOSPHOR BRONZE, GOLD	NYLON,UL94V-0,WHITE	350787-2
PHOSPHOR BRONZE, PRE-TIN	NYLON,UL94V-0,WHITE	350787-1
PIN CONTACT MATERIAL AND FINISH	HOUSING MATERIAL	PART NUMBER



THIS DRAWING IS A CONTROLLED DOCUMENT.		REV	DATE	BY	CHK	APP
UNLESS OTHERWISE SPECIFIED:	UNIT: MILLIMETERS	1	02-14
SCALE: 1:1	PROJECTION: FIRST ANGLE	DATE CODE	DRAWING NO.	REVISED TO	REVISED BY	REVISED DATE
SEE TABLE	SEE TABLE	---	A100778	350787	---	---
CUSTOMER DRAWING		REV	DATE	BY	CHK	APP
		5.1				