THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
© COPYRIGHT By - ALL RIGHTS RESERVED.

UNI	CHT	REVISIONS				
CM	00	P	LTR	DESCRIPTION	DATE	EBR	APVD
			M1	REVISED PER ECO-11-004820	11MAR11	RK	HMR

1. PARTS MUST COMPLY WITH AMP SOLDERABLITY SPEC 109-11-3.
2. CONTACT IS STAMPED FROM PRE-PLATED STOCK WHICH IS PLATED OVERALL WITH 0.00127 [.000050] NICKEL, THEN STRIPED WITH 0.00076 [.000030] GOLD IN CONTACT AREA INDICATED AND TIN-LEAD ON SOLDER TAIL END.
3. CIRCUIT IDENTIFICATION CHARACTERS ARE ADJACENT TO THE INDICATED CAVITIES, BUT LOCATION AND ORIENTATION MAY DIFFER FROM PRINT.
4. CONTACT IS PLATED OVERALL WITH 0.00127 [.000050] NICKEL, THEN 0.00076 [.000030] GOLD OVER CONTACT LENGTH INDICATED AND MATTE TIN ON SOLDER TAIL END.





RECOMMENDED LAYOUT FOR 1.58 [.062] THICK PC BOARD

CONTACT	HOUSING	PART NO
PH BRZ GOLD 4	NYLON,UL 94V-0	350827-4
PH BRZ GOLD 2	NYLON,UL 94V-0	350827-2
PH BRZ TIN	NYLON,UL 94V-0	350827-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DRN K. WHITAKER 11OCT2005
CHK S. RIDGILL 11OCT2005
APP S. RIDGILL 11OCT2005
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

TE Connectivity

6 CIRCUIT UNIVERSAL MATE-N-LOK (TM) P.C. BOARD SOCKET HEADER ASSEMBLY

SIZE A1 | CAGE CODE 00779 | DRAWING NO C-350827 | RESTRICTED TO

CUSTOMER DRAWING | SCALE 5:1 | SHEET 1 OF 1 | REV M1

METRIC

4808 (3/11)

Downloaded from Elcodis.com electronic components distributor