

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.




MATERIAL:
 HOUSING: THERMOPLASTIC PA, UL94V-0, BLACK.
 TERMINAL: BRIGHT TIN PLATED, COPPER ALLOY.
 SCREW: 6-32, STEEL, ZINC PLATED CLEAR CHROMATE.

ELECTRICAL:
 UL CLASS C: 20A, 150V.
 UL CLASS D: 10A, 300V.
 CSA TYPE B: 20A, 300V.
 CSA TYPE C: 20A, 300V.
 CSA TYPE D: 10A, 300V.
 CSA TYPE E: 20A, 300V.
 WIRE RANGE: 12-22 AWG

△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

MECHANICAL:
 MAXIMUM TORQUE RATING: 7 IN-LBS.
 RUNNING TORQUE: 0.5-3.5 IN-LBS UNLESS OTHERWISE STATED.

- ① SCREWS ARE BOTTOMED, NO THREAD INTERRUPT.
- ② SCREWS ARE NICKEL PLATED BRASS.
- ③ SCREWS ARE CAPTIVE.
- ④ SEE FIGURE.
- ⑤ PRELIMINARY PART NUMBER.



RECOMMENDED PCB LAYOUT

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
FT	0						
		N3		REVISED PER ECO-11-004587	11MAR11	RK	HMR
⑤ ④	.160			4DB-P108-18	5.915	18	4-1437667-4
	.160			4DB-P108-16-105	5.590	17	2-796628-4
	.160			4DB-P108-17	5.590	17	4-1437667-2
	.160			4DB-P108-16	5.265	16	4-1437667-0
	.160			4DB-P108-15	4.940	15	3-1437667-9
② ①	.160			4DB-P108-14-102	4.615	14	2-796658-5
②	.160			4DB-P108-14-102	4.615	14	2-796658-3
	.160			4DB-P108-14	4.615	14	3-1437667-8
	.160			4DB-P108-13	4.290	13	3-1437667-7
	.160			4DB-P108-12	3.965	12	3-1437667-6
	.160			4DB-P108-11	3.640	11	3-1437667-5
	.160			4DB-P108-10	3.315	10	3-1437667-3
⑤ ②	.160			4DB-P106-09-094	2.990	9	1-796658-7
	.160			4DB-P108-09	2.990	9	3-1437667-2
⑥ ①	OBsolete	.160		4DB-P108-08-091	2.665	8	1-796658-4
	.160			4DB-P108-08	2.665	8	3-1437667-1
⑤ ③ ②	.160			4DB-P106-07-100	2.340	7	2-796658-2
	.160			4DB-P106-07-093	2.340	7	1-796658-6
	.160			4DB-P108-07	2.340	7	3-1437667-0
⑤ ③ ②	.160			4DB-P106-06-099	2.015	6	2-796658-1
⑥ ①	OBsolete	.160		4DB-P108-06-090	2.015	6	1-796658-3
⑤	.200			4DB-P108-06	2.015	6	2-796658-6
	.160			4DB-P108-06	2.015	6	2-1437667-9
⑤ ③ ②	.160			4DB-P106-05-098	1.690	5	2-796658-0
⑥ ④	OBsolete	.160		4DB-P108-05-093	1.690	5	1-796658-5
	.160			4DB-P108-05	1.690	5	2-1437667-8
⑤ ③ ②	.160			4DB-P106-04-097	1.365	4	1-796658-9
①	.160			4DB-P108-04-089	1.365	4	1-796658-2
	.160			4DB-P108-04	1.365	4	2-1437667-6
⑤ ③ ②	.160			4DB-P106-03-096	1.040	3	1-796658-8
⑥ ①	.160			4DB-P108-03-088	1.040	3	1-796658-1
	.160			4DB-P108-03	1.040	3	2-1437667-5
	.160			4DB-P108-02	.715	2	2-1437667-4

DIM B	CATALOG NUMBER	DIM A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S WELDON 01MAY2003	 TE Connectivity ASSEMBLY, DUAL BARRIER 4DB-P108-XX		
DIMENSIONS: INCHES		CHK S YODER 5/1/03			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S YODER 5/1/03			
0 PLC ± - 1 PLC ± - 2 PLC ± .01 3 PLC ± .005 4 PLC ± - ANGLES ± 1°		NAME			
MATERIAL	FINISH	SIZE A3	CAGE CODE 00779	DRAWING NO C-2-1437667-4	RESTRICTED TO
		CUSTOMER DRAWING		SCALE NTS	SHEET 1 of 2
				REV N3	

4


3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
-	-	SEE SHEET 1	-	-	-	



2-796658-4

.160	4DB-P108-30	9.815	30	5-1437667-5
.160	4DB-P108-29	9.490	29	796658-9
.160	4DB-P108-28	9.165	28	5-1437667-3
.160	4DB-P108-27	8.840	27	796658-8
.160	4DB-P108-26	8.515	26	5-1437667-2
.160	4DB-P108-25	8.190	25	796658-7
.160	4DB-P108-24	7.865	24	5-1437667-0
.160	4DB-P108-23	7.540	23	796658-6
.160	4DB-P108-22	7.215	22	4-1437667-8
.160	4DB-P108-21	6.890	21	796658-2
.160	4DB-P108-20	6.565	20	4-1437667-6
.160	4DB-P108-19	6.240	19	4-1437667-5
DIM B	CATALOG NUMBER	DIM A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S WELDON 01MAY2003	STE TE Connectivity	
DIMENSIONS: INCHES		CHK S YODER 5/1/03		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S YODER 5/1/03	NAME	
0 PLC ± -		PRODUCT SPEC	ASSEMBLY, DUAL BARRIER	
1 PLC ± -		APPLICATION SPEC	4DB-P108-XX	
2 PLC ± .01		WEIGHT	SIZE A3	CAGE CODE C-2-1437667-4
3 PLC ± .005		MATERIAL	DRAWING NO	RESTRICTED TO
4 PLC ± -		FINISH	SCALE NTS	SHEET 2 of 2
ANGLES ± 1°		CUSTOMER DRAWING	REV N3	