

4

3

2

1




THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

MATERIAL:  
 HOUSING: THERMOPLASTIC, UL94V-0 BLACK.  
 TERMINALS: BRIGHT TIN PLATED, COPPER ALLOY.  
 SCREWS: 6-32, STEEL, ZINC PLATED WITH CLEAR CHROMATE.  
 UNLESS OTHERWISE NOTED.





ELECTRICAL:  
 RATED CURRENT UL/CSA:  
 CLASS C: 25A, 300V.  
 CLASS D: 5A, 600V.  
 WIRE RANGE: 12-22 AWG

MECHANICAL:  
 RECOMMENDED TIGHTENING TORQUE: 7 IN.-LBS.  
 OPERATING TEMP.: 105°C MAX

- △ MARK WITH WHITE PERMANENT INK.
- 2 ALL SCREWS TO BE DRIVEN DOWN TO TERMINAL SURFACE.
- 3 STAINLESS STEEL SCREWS.
- 4 NICKEL PLATED BRASS SCREWS.
- 5 PRELIMINARY PART NUMBER.



SEE TABLE FOR P/N'S



LOC	DIST	REVISIONS					
FT	0	P	LTR	DESCRIPTION	DATE	BY	APPD
		C4		REVISED PER ECO-11-014076	12JUL11	HMR	CR

REVISIONS	NO OF CHG	DATE	BY	APPD
11.311	30	6PCV-30-007	8-1546158-7	
11.311	30	6PCV-30-007	1546814-2	
10.936	29	6PCV-29-007	1546814-1	
10.561	28	6PCV-28-007	2-1546686-1	
10.186	27	6PCV-27-007	2-1546686-0	
9.811	26	6PCV-26-007	8-1546158-4	
9.436	25	6PCV-25-007	1-1546686-9	
9.061	24	6PCV-24-723	3-1437654-8	
9.061	24	6PCV-24-007	8-1546158-3	
8.686	23	6PCV-23-007	1-1546686-8	
8.311	22	6PCV-22-007	1-1546686-7	
7.936	21	6PCV-21-007	1-1546686-6	
7.561	20	6PCV-20-720	2-1437654-7	
7.561	20	6PCV-20-1360	7-1546158-7	
7.561	20	6PCV-20-1359	7-1546158-6	
7.561	20	6PCV-20-007	7-1546158-3	
7.186	19	6PCV-19-007	1-1546686-5	
6.811	18	6PCV-18-1390	1546262-5	
6.811	18	6PCV-18-007	1437654-8	
6.436	17	6PCV-17-1206	1437654-1	
6.436	17	6PCV-17-007	1-1546686-4	
6.061	16	6PCV-16-719	9-1437653-4	
6.061	16	6PCV-16-007	8-1437653-1	
5.686	15	6PCV-15-993	7-1437653-6	
5.686	15	6PCV-15-007	7-1437653-5	
5.311	14	6PCV-14-1205	7-1437653-0	
5.311	14	6PCV-14-007	6-1437653-7	
4.936	13	6PCV-13-1194	6-1437653-5	
4.936	13	6PCV-13-007	6-1546158-7	
4.561	12	6PCV-12-718	5-1437653-8	
4.561	12	6PCV-12-007	5-1437653-2	
4.186	11	6PCV-11-007	1-1546686-3	
3.811	10	6PCV-10-003	6-1546158-1	
3.811	10	6PCV-10-1193	3-1437653-8	
3.811	10	6PCV-10-007	3-1437653-6	
3.436	9	6PCV-09-003	5-1546686-5	
3.436	9	6PCV-09-1270	2-1437653-8	
3.436	9	6PCV-09-007	2-1437653-6	
3.061	8	6PCV-08-1397	5-1546686-4	
3.061	8	6PCV-08-717	1-1437653-9	
3.061	8	6PCV-08-007	1-1437653-4	
2.686	7	6PCV-07-007	1437653-8	
2.311	6	6PCV-06-716	1437653-1	
2.311	6	6PCV-06-007	9-1437652-6	
2.311	5	6PCV-06-1173	6-1546686-1	
1.936	5	6PCV-05-1341	6-1437652-6	
1.936	5	6PCV-05-007	6-1546686-3	
1.561	4	6PCV-04-715	7-1437652-5	
1.561	4	6PCV-04-007	6-1437652-8	
1.186	3	6PCV-03-1256	4-1546158-7	
1.186	3	6PCV-03-003	1546119-2	
1.186	3	6PCV-03-007	5-1437652-5	
.811	2	6PCV-02-1395	5-1546686-2	
.811	2	6PCV-02-1339	4-1437652-6	
.811	2	6PCV-02-007	4-1437652-0	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES 0 PLC ± .010 1 PLC ± .005 2 PLC ± .011 3 PLC ± .005 4 PLC ± .010 ANGLES ± .1° FINISH	DIM: S. SCHLEGEL 23MR03 OK: S. YODER 4/23/04 NAME: S. YODER PRODUCT SPEC: 4/23/04 APPLICATION SPEC: WEIGHT: CUSTOMER DRAWING	DIM A NO OF POS CATALOG NUMBER PART NO 6PCV-XX-007 ASSEMBLY SIZE CASE CODE DRAWING NO: A2 00779 C-4-1437652-0 RESTRICTED TO: NTS SCALE: NTS SHEET 1 of 1 REV: C4
---	--	--

4-1437652-0

A