



- △ HOUSING: FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK
- △ CONTACTS: PHOS BRONZE
- △ INSERTS & SCREWLOCKS: ZINC
- △ REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.
- △ CONTACTS: SEE TABLE
- △ INSERTS & SCREWLOCKS: CLEAR CHROMATE COATING.
- △ PLATED WITH GOLD FLASH FOR LENGTH OF .055 MIN FROM MATING END, .000100 MIN TIN ON SOLDER END, ALL OVER .000050 MIN NICKEL ON ENTIRE CONTACT.
- △ PLATED WITH .000030 MIN GOLD FOR LENGTH OF .055 MIN FROM MATING END, .000100 MIN TIN SOLDER END, ALL OVER .000050 MIN NICKEL ON ENTIRE CONTACT.

WITH SCREWLOCKS	△ 4	△ 5	5747460-5
WITH INSERTS	△ 4	△ 5	5747460-4
WITH INSERTS	△ 4	△ 5	5747460-3
WITH .120 DIA HOLE	△ 4	△ 5	5747460-2
WITH .120 DIA HOLE	△ 4	△ 5	5747460-1
REMARKS	FINISH	FAIRY NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT		DESIGNED BY: J. PETERS	CHECKED BY: M. BOLASH	DATE: 10B-40025	REVISED BY: M. BOLASH	DATE: 114-40015	REVISED BY: A1	DATE: 00779	REVISED BY: G	DATE: 5747460	
DRAWING NO: 10B-40025		REVISED BY: M. BOLASH		DATE: 114-40015		REVISED BY: A1		DATE: 00779		REVISED BY: G	
DESCRIPTION: RECEPTACLE ASSY, SIZE 2, 15 POSN, RIGHT ANGLE, 500 SERIES, .026 DIA POSTS, AMPULITE HC-20		DRAWING NO: 10B-40025		REVISED BY: M. BOLASH		DATE: 114-40015		REVISED BY: A1		DATE: 00779	
CUSTOMER DRAWING		DATE: 114-40015		REVISED BY: A1		DATE: 00779		REVISED BY: G		DATE: 5747460	