THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -.-.-
© COPYRIGHT - By - ALL RIGHTS RESERVED

UOC	DIST
GP	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	REVISED PER ECO-11-009374	23MAY2011	CJV	SLB



1. HOUSING: NYLON OR POLYESTER, FRAME RETARDANT, UL 94V-0 RATED, GLASS FILLED, BLACK.
   CONTACTS: BRASS.
   SHELL: CARBON STEEL.
   EYELETS: BRASS.
   SCREWLOCKS: ZINC.
   BOARDLOCKS: COPPER ALLOY.
2. SHELL: 2.54µm[.000100] MIN TIN OVER 1.27µm[.000050] MIN COPPER.
   EYELETS: 2.54µm[.000100] MIN TIN OVER COPPER FLASH.
   BOARDLOCKS: 3.81µm[.000150] MIN TIN OVER 1.27µm[.000050] MIN NICKEL.
   CONTACTS: 0.76µm[.000030] MIN GOLD PLATE ON THE MATING SURFACES, 2.54µm[.000100] MIN TIN PLATE ON THE SOLDER END, 1.27µm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
   -OR-
   GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.76µm[.000030] MIN TOTAL ON THE MATING SURFACES, 2.54µm[.000100] MIN TIN PLATE ON THE SOLDER END, 1.27µm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
   SCREWLOCKS: CLEAR CHROMATE.
3. DIMENSION APPLIES FROM CENTER OF CONTACTS.





RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS
P.C. BOARD THICKNESS: 1.57[.062]

COPYRIGHT 2005
TYCO ELECTRONICS CORP
ALL RIGHTS RESERVED

THIS DRAWING IS A CONTROLLED DOCUMENT.	TPR L. VARELA – DOCKS 04-07-05	TE Connectivity	5747850-6
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – 1 PLC ± – 2 PLC ± – 3 PLC ± 0.13[.005] 4 PLC ± – ANGLES ± 2°	CHK S. BOLASH 04-27-05	PART NUMBER
		APVD M. WALMSLEY 04-27-05	NAME PLUG ASSEMBLY, SIZE 3, 25 POSITION, RIGHT ANGLE, FRONT METAL SHELL, .478 SERIES, BOARDLOCKS, AMPLIMITE HD-20
		PRODUCT SPEC 108-40025	
		APPLICATION SPEC 114-40010	SIZE A1 CAGE CODE 00779 DRAWING NO C-5747850 RESTRICTED TO –
MATERIAL 1	FINISH 2	WEIGHT –	CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV B

4805 (3/11)

Downloaded from Elcodis.com electronic components distributor