




C.A.D. FILE CODE
5. C344989.A

DO NOT SCALE

DIMENSIONS IN MM.



SECTION C C.



SECTION D D.


WIRE RANGE 2.00 TO 3.00 MM²
INS. RANGE 4.10 TO 5.50 MM DIA. INC. SEAL
(ONLY THIN WALLED CABLE 2.60 TO 3.40 MM DIA. IS SUITABLE)

PRODUCT SPEC. 108-3069

APPLICATION SPEC. 114-3036

H/TOOL PN.525316-1 (FOR 2mm² AND 2.5 TO 3mm² WIRES)

SEALED APPLICATIONS ONLY

PRE-TINNED BRASS		MADE FROM STRIP PN.344008-1		344989-1	
FINISH		MATERIAL		PART NUMBER	
CUSTOMER DWG FOR REFERENCE ONLY		© COPYRIGHT 1991 BY AMP OF GREAT BRITAIN LTD. ALL INTERNATIONAL RIGHTS RESERVED. ALL PRODUCTS MAY BE COVERED BY BRITISH AND FOREIGN PATENTS AND/OR PATENTS PENDING.		RELEASED FOR PUBLICATION 25 SEP 1991	
-	-	TOLERANCES UNLESS OTHERWISE STATED		DR. R. J. S. 25.9.91	
-	-	DEC ± 0.5		CH. <i>Wain</i> 26/11/91 APP. J.P.	
-	-	ANGLES ± 1°		 TERMINAL HOUSE STANNORE MIDDX.	
A EB00-0031-01 (4.02.01)		NAME .250 SERIES TAB (LOOSE PIECE) ECONOSEAL 3 H.C. (SEALED)			
1	PRELIM. ISSUE	25.9.91	SCALE	LOC	SIZE
REV	APPROVED	ECH	DATE	4/1	E A3
			DWG.No.	REV	SHEET
			C344989	A	1/1