



- NOTES:
- 1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
 - OUTER DIMENSIONS OF INSULATION: MAX. Ø3.2 MM
 - SUITABLE HOOD SIZE 4: SERIES HB, HD, HP, EMV
 - SUITABLE INSERTION AND EXTRACTION TOOL: SCREWDRIVER 0.5x3 DIN 5264
 - Strip length: Screw connection 10mm
 - Spring clamp connection 10mm Crimp connection 7.5mm
 - STANDARDS: DIN EN 61984; DIN EN 60664-1
 - PACKAGING: 5 SETS IN A CARTON, PRE-MOUNTED
 - SPECIAL PACKAGING: Krauss-Maffei
 - PACKAGING UNIT: 256 PIECES

QTY	DESCRIPTION	MATERIAL	SURFACE	COLOR	ITEM NO. POS.	REMARKS
4	fixing screw	stainless steel	even		10	M3x10
4	fixing screw	steel	nickel plated	blue	9	M3x10
10	contact socket spring clamp	brass	gold plated		8	
	contact socket spring clamp	brass	silver plated		7	
	contact socket screw version	brass	gold plated		6	
	contact socket screw version	brass	silver plated		5	
1	cover spring clamp version			light grey	4	
	cover crimp version			light grey	3	
1	cover screw version			light grey	2	
1	socket insert			light grey	1	

ORDERING TEXT / BESTELLTEXT	<p>THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION. DIESE ZEICHNUNGSDOKUMENT WIRD DURCH AMP INCORPORATED KONTROLLIERT. ÄNDERUNGEN, DIE DEN TECHNISCHEN FORTSCHRITT DENERN, SIND VORBEHALTEN. DEN JEWELIGEN LETZTLICHEN ÄNDERUNGEN SIND DRUCKER BEI AMP ANFANG.</p> <p>DIMENSIONS: DIMENSIONEN: (mm)</p> <p>TOLERANCES UNLESS OTHERWISE SPECIFIED: ALLGEMEINTOLERANZEN</p> <p>A. ISO 8015</p> <p>B. ISO 2768 - mH - E</p> <p>C. DIN 16901 - 12.0</p> <p>0 PLC</p> <p>1 PLC</p> <p>2 PLC</p> <p>3 PLC</p> <p>ANGLES / WINKEL</p> <p>FINISH / OBERFLÄCHE / FARBE</p>	<p>DOWN: 09.02.99</p> <p>APVO: 18.02.99</p> <p>Gräf</p> <p>Chr</p> <p>Schweiger</p> <p>NAME: HTS Elektrotechnik</p> <p>53819 Neunkirchen, Germany</p> <p>PRODUCT SPEC: Buchseneinsatz HE.10.Bu</p> <p>APPLICATION SPEC: DRAWING NO. 1103637</p> <p>WEIGHT: A3</p> <p>GEWICHT: 00779</p> <p>CUSTOMER DRAWING: /KUNDENZEICHNUNG</p> <p>SCALE: MASSSTAB 1:1</p> <p>SHEET: BLATT 1</p> <p>OF: VON 1</p> <p>REV: A8</p>
-----------------------------	--	--