



DESIGNED FOR USE WITH RG-316/U, 179, 187, 188 CABLES	
CABLE ENTRY DIAMETER MINIMUM	.067
HOUSING	.125
FERRULE	.023
CONTACT	

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01	REVISED	10/31/95	ICom 11/9/95

**DESIGN CONTROL REQUIRED**

COMPONENT	MATERIAL	FINISH
HOUSING BUSHING SPRING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT SLEEVE	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT RING SHIM	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	NICKEL PLATE PER QQ-N-290
RETAINING CLIP	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	GOLD PLATE PER MIL-G-45204
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions Per MIL-STD-348A Fig. 3212	Temperature Rating -65° to +125°C
Frequency Range (GHz) DC to 18	Mating Characteristics:	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX) 250	Insertion (MAX Lbs) 3	Shock MIL-STD-202, Method 213, Condition I
Sea Level	Withdrawal (MIN Oz) 1	Thermal Shock MIL-STD-202, Method 107, Condition B
VSWR 1.15-0.1F(GHz)	Force to Engage (In/Lbs MAX) 3	Moisture Resistance MIL-STD-202, Method 106
Insertion Loss (dB MAX) .03x√f(GHz)	& Disengage (In/Lbs MAX) 15	Corrosion - MIL-STD-202, Method 101, Condition B
RF Leakage (dB MIN) Interface Only, Fully Mated -90-f(GHz)	Center Contact Captivation Axial (Lbs) 6	
Corona, 70,000 Ft (VRMS MIN) 190	Cable Retention Axial Force (Lbs MIN) 20	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Weight (Grams) TBD	
Contact Resistance (Milliohms MAX) Center Contact 2.0		
Outer Contact 2.0		
Cable to Housing 0.5		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500		
IR.(Megohms MIN) 5000		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		DRAWN BY RNF DATE 2/13/95		AMP Incorporated	
FRAC. DEC. ANGLES ± 1/64 ± .005 ± °		CHECKED BY		140 Fourth Avenue	
These drawings and specifications are the property of N/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.		APPROVED BY RNF DATE 2/13/95		Waltham, MA 02451-7599	
USE ASSY PROCEDURE		NO. AP. 408-08273 (45-020)		TITLE OSP FLOATING PANEL FEEDTHRU REAR MOUNT CABLE JACK - CRIMP ATTACHMENT	
SIZE B	CODE IDENT NO. 26805	1250-2262-02	REV 01		
SCALE 2:1			SHEET 1 OF 1		

CUSTOMER DRAWING AMP PART # 1046300-1 SHEET 1 OF 1 REV A