THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
IN	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D	REV PER ECR-06-007120	31MAR2006	MBH	AV
	D1	REV PER ECR-10-012887	18JUN2010	VSS	MB



1438761-6
KEY "A"
GRAY



1438759-1
KEY "B"
WHITE



SCALE 3:1



2.8 CONTACT CIRCUIT 1
040 CONTACT CIRCUIT 13

SCALE 3:1







NOTES:

1. APPLIED CONTACT PART NUMBERS:
   175265 TIN PLATING, 040 CONTACT
   175266 SELECT GOLD PLATING, 040 CONTACT
   1326030 TIN PLATING, 2.8 CONTACT

2. LOCK PLATE SHOWN IN THE SHIPPING POSITION.

3. VISUAL BLEMISHES MAY BE PRESENT ON EXTERNAL SURFACES DUE TO BULK PACKAGING METHODS. THESE BLEMISHES THAT DO NOT AFFECT CONNECTOR FORM, FIT, OR FUNCTION ARE CONSIDERED ACCEPTABLE.

4. LOCK PLATE COMPONENT FORCES:
   INSERTION FORCE (SEATING): 75N MAX.
   REMOVAL FROM PLUG HOUSING: 15N MIN.

-KEY "B" SHOWN-

DWN M. HITCHCOCK 16SEP2004	Tyco Electronics Harrisburg, PA 17105-3608		
CHK G. MARTIN 16SEP2004			
APVD T. MEHAFFEY 16SEP2004	NAME 22-WAY HYBRID PLUG ASSEMBLY		
PRODUCT SPEC 108-2217			
APPLICATION SPEC 114-13158	SIZE A2	CAGE CODE 00779	DRAWING NO C-1438759
WEIGHT -	RESTRICTED TO -		
CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1	REV D1

DIMENSIONS: mm
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±0.0, 1 PLC ±0.3, 2 PLC ±0.1, 3 PLC ±0.0000, 4 PLC ±0.00000, ANGLES ±1
MATERIAL PBT
FINISH -

AMP 1471-9 REV 31MAR2000
Pro/ENGINEER DRAWING

Downloaded from Elcodis.com electronic components distributor