



1. PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TE CONNECTIVITY STANDARD 230-702.
2. CABLE ASSEMBLY TO BE 100% TESTED FOR OPENS, SHORTS AND CONTINUITY
 HI-HOT: 200 VDC FOR 100ms
 INSULATION RESISTANCE: 50M OHMS MIN
 CONTINUITY RESISTANCE: 2 OHMS MAX
 FREQUENCY RANGE: DC TO 6 GHz
 VSWR: 1.5:1 MAX

2.0	50.0	2015698-4
3.0	200.0	2015698-3
2.0	100.0	2015698-2
2.0	39.0	2015698-1
TOLERANCE "T" mm	LENGTH "A" mm	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN E.C. CLAYBAUGH 18/DEC/07	TE Connectivity		
DIMENSIONS: mm		CHK J. ORNER 18/DEC/07			
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APVD J. ORNER 18/DEC/07	NAME CABLE ASSY, UMCC R/A TO UMCC R/A, TYPE II, 0.80mm CABLE		
MATERIAL		PRODUCT SPEC	SIZE A3	CAGE CODE 00779	DRAWING NO C-2015698
FINISH		APPLICATION SPEC	RESTRICTED TO		
		WEIGHT	SCALE N.T.S.		
		CUSTOMER DRAWING		SHEET 1 of 1	
				REV A1	