



- ▲ REELED FOR USE WITH STANDARD APPLICATORS.
- ▲ REELED FOR USE WITH HEAVY DUTY MINI-APPLICATORS.
- ▲ PLATED WITH .000100 MIN SILVER PER Q.Q-S-345.
- ▲ PLATED WITH .000015 MIN GOLD PER MIL-G-45204 IN THE LOCALIZED GOLD PLATE AREA, GOLD FLASH ON THE REMAINDER, OVER .000030 MIN NICKEL PER Q.Q-N-290.
- ▲ PLATED WITH .000030 MIN GOLD PER MIL-G-45204 IN THE LOCALIZED GOLD PLATE AREA, GOLD FLASH ON THE REMAINDER, OVER .000030 MIN NICKEL PER Q.Q-N-290.
- ▲ PLATED WITH .000050 MIN 93-7% TIN-LEAD ALLOY OVER .000030 MIN NICKEL PER Q.Q-N-290.
- 7. WIRE RANGE = 10 AWG.
- 8. INSULATION RANGE = .190 - .220 DIA.
- ▲ PLATED TIN (NO LEAD), .000050 MIN THK PER ASTM-B-345 OVER NICKEL .000030 MIN THK PER Q.Q-N-290.

TERMINAL LATCH COLOR	FINISH	STRIP ASSY P/N REF	STRIP ASSY P/N REF	LOOSE PIECE P/N ASSY
BLACK	▲	1-66253-0	66253-9	66259-5
NATURAL	▲	66253-8	66253-4	66259-4
BLACK	▲	66253-7	66253-1	66259-3
BLACK	▲	66253-6	66253-2	66259-2
BLACK	▲	66253-5	66253-1	66259-1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ON: DECIMALS ±.010 ANGLES ±.010		CONTRACT NO		TE Connectivity MALE TYPE XII CONTACT LOOSE PIECE ASSY	
MATERIAL SEE CALLOUT		DR: <i>Rick Hollenbeck</i> 7-27-05 CHG: <i>Larry G. Lawrence</i> 10-1-85 APPD: <i>Bob Ballard</i> 12-1-85 APPD: <i>Kevin E. Smith</i> 10-3-88			
FINISH SEE DASH NO		OTHER APPD		SIZE C	FSCM NO 00779
				DRAWING NO 66259	SHEET

CUSTOMER DRAWING

66259