



PIN ASSIGNMENT

PIN	SYMBOL	PIN	SYMBOL
1	CS1	15	VOUT
2	RES	16	CAP3P
3	A0	17	CAP1N
4	WR	18	CAP1P
5	RD	19	CAP2P
6	D0	20	CAP2N
7	D1	21	V4
8	D2	22	V3
9	D3	23	V2
10	D4	24	V1
11	D5	25	V0
12	D6	26	C86
13	D7	27	P/S
14	VSS	28	VDD

1. ALL DIMENSIONS ARE IN mm WITH 0.20 TOLERANCE UNLESS OTHERWISE SPECIFIED
2. VIEWING ANGLE: 6:00 O' CLOCK
3. POLARIZER TYPE: TRANFLECTIVE, POSITIVE
4. DISPLAY TYPE:FSTN
5. OPERATING VOLTAGE: 2.4V ~ 3.3V
6. DRIVE MOKE: 1/64 DUTY, 1/9 BIAS, Vop9.0V
7. OPERATING TEMPERATURE: -10°C ~ +60 °C
8. STOPAGE TEMPERATURE: -20°C ~ +70 °C
9. CONNECTOR: COG ST7565P

Reinforcement Board
Conductor Side

TS DISPLAY

DRAWING TITLE:		
DRAWING NUMBER: TSG12864C03		DWN: JACK
		DATE: 2007-05-24
SCALE:	REV: 00	SHEET: 1 OF 1