



| | | | | | | | | | | |
|--------|-----|-----|----|----|-----|-----|------|------|------|------|
| PIN | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| SYMBOL | VSS | VDD | V0 | RS | R/W | E | D0 | D1 | D2 | D3 |
| PIN | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| SYMBOL | D4 | D5 | D6 | D7 | CS1 | CS2 | /RET | VOUT | LEDA | LEDK |

NOTES:

1. DISPLAY TYPE: STN/YELLOW-GREEN-POSITIVE
2. OPERATING VOLTAGE: 5V
3. OPERATING TEMPERATURE: -0°C~50°C
4. STORAGE TEMPERATURE: -10°C~60°C
5. DRIVE MODE: 1/64D,1/9B
6. VIEWING DIRECTION: 6:00
7. POLARIZER TYPE:
8. CONNECTOR: ZEBRA

T S DISPLAY

| | | | |
|-----------|---------|----------|------------|
| Dwg Title | | | |
| TSM12864A | | | |
| Dwg No. | | | Date |
| | | | 2004-10-21 |
| Scale | Unit | Tol. | |
| | mm | ±0.2 | |
| Drawn | Checked | Approved | |
| LIU | | | |