


SKiiP 513GD172-3DUL



SKiiP® 3

6-pack-integrated intelligent Power System

Power section


SKiiP 513GD172-3DUL

Data

Power section features

- SKiiP technology inside
- Trench IGBTs
- CAL diode technology
- Integrated current sensor
- Integrated temperature sensor
- Integrated heat sink
- IEC 60721-3-3 (humidity) class 3K3/IE32 (SKiiP® 3 System)
- IEC 60068-1 (climate) 40/125/56
- UL recognized file no. E63532

1) with assembly of suitable MKP capacitor per terminal



Case S33


| Absolute Maximum Ratings | | $T_s = 25^\circ\text{C}$ unless otherwise specified | |
|--------------------------|--|---|-------------------|
| Symbol | Conditions | Values | Units |
| IGBT | | | |
| V_{CES} | Operating DC link voltage | 1700 | V |
| $V_{CC}^{(1)}$ | | 1200 | V |
| V_{GES} | | ± 20 | V |
| I_C | $T_s = 25 (70)^\circ\text{C}$ | 500 (375) | A |
| Inverse diode | | | |
| $I_F = -I_C$ | $T_s = 25 (70)^\circ\text{C}$ | 400 (300) | A |
| I_{FSM} | $T_j = 150^\circ\text{C}$, $t_p = 10\text{ ms}$; sin | 3500 | A |
| I^{2t} (Diode) | Diode, $T_j = 150^\circ\text{C}$, 10 ms | 61 | kA ² s |
| T_j , (T_{stg}) | | - 40 ... + 150 (125) | $^\circ\text{C}$ |
| V_{isol} | rms, AC, 1 min, main terminals to heat sink | 4000 | V |
| $I_{AC\text{-terminal}}$ | per AC terminal, rms, $T_s = 70^\circ\text{C}$, $T_{terminal} < 115^\circ\text{C}$ | 400 | A |

| Characteristics | | $T_s = 25^\circ\text{C}$ unless otherwise specified | | | | | | | |
|---|---|---|-----------|-----------|------------|-----|------|------|------|
| Symbol | Conditions | min. | typ. | max. | Units | | | | |
| IGBT | | | | | | | | | |
| V_{CEsat} | $I_C = 300\text{ A}$, $T_j = 25 (125)^\circ\text{C}$; measured at terminal | | 1,9 (2,2) | 2,4 | V | | | | |
| V_{CEO} | $T_j = 25 (125)^\circ\text{C}$; at terminal | | 1 (0,9) | 1,2 (1,1) | V | | | | |
| r_{CE} | $T_j = 25 (125)^\circ\text{C}$; at terminal | | 3 (4,1) | 3,9 (5) | m Ω | | | | |
| I_{CES} | $V_{GE} = 0\text{ V}$, $V_{CE} = V_{CES}$, $T_j = 25 (125)^\circ\text{C}$ | | 1,2 (72) | | mA | | | | |
| $E_{on} + E_{off}$ | $I_C = 300\text{ A}$, $V_{CC} = 900\text{ V}$ | | 195 | | mJ | | | | |
| | $T_j = 125^\circ\text{C}$, $V_{CC} = 1200\text{ V}$ | | 288 | | mJ | | | | |
| R_{CC+EE} | terminal chip, $T_j = 25^\circ\text{C}$ | | 0,5 | | m Ω | | | | |
| L_{CE} | top, bottom | | 12 | | nH | | | | |
| C_{CHC} | per phase, AC-side | | 1,7 | | nF | | | | |
| Inverse diode | | | | | | | | | |
| $V_F = V_{EC}$ | $I_F = 300\text{ A}$, $T_j = 25 (125)^\circ\text{C}$; measured at terminal | | 1,9 (1,7) | 2,4 | V | | | | |
| V_{TO} | $T_j = 25 (125)^\circ\text{C}$ | | 1,1 (0,8) | 1,4 (1,1) | V | | | | |
| r_T | $T_j = 25 (125)^\circ\text{C}$ | | 2,6 (2,9) | 3,4 (3,7) | m Ω | | | | |
| E_{rr} | $I_C = 300\text{ A}$, $V_{CC} = 900\text{ V}$ | | 36 | | mJ | | | | |
| | $T_j = 125^\circ\text{C}$, $V_{CC} = 1200\text{ V}$ | | 43 | | mJ | | | | |
| Mechanical data | | | | | | | | | |
| M_{dc} | DC terminals, SI Units | | 6 | 8 | Nm | | | | |
| M_{ac} | AC terminals, SI Units | | 13 | 15 | Nm | | | | |
| w | SKiiP® 3 System w/o heat sink | | 2,4 | | kg | | | | |
| w | heat sink | | 7,5 | | kg | | | | |
| Thermal characteristics (PX 16 heat sink with fan SKF16B-230-1); "s" reference to heat sink; "r" reference to built-in temperature sensor (acc.IEC 60747-15) | | | | | | | | | |
| $R_{th(j-s)I}$ | per IGBT | | | 0,059 | K/W | | | | |
| $R_{th(j-s)D}$ | per diode | | | 0,115 | K/W | | | | |
| Z_{th} | R_i (mK/W) (max. values) | tau _i (s) | | | | | | | |
| | | 1 | 2 | 3 | 4 | | | | |
| $Z_{th(j-r)I}$ | | 10,2 | 28,8 | 21 | 0 | 363 | 0,18 | 0,04 | 1 |
| $Z_{th(j-r)D}$ | | 36 | 36 | 54 | 60 | 30 | 5 | 0,25 | 0,04 |
| $Z_{th(r-a)}$ | | 2,1 | 20 | 5,5 | 1,4 | 210 | 85 | 11 | 0,4 |

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of

our personal.

SKiiP 513GD172-3DUL



SKiiP® 3

6-pack-integrated intelligent Power System

6-pack integrated gate driver SKiiP 513GD172-3DUL

Data

Gate driver features


- CMOS compatible inputs
- Wide range power supply
- Integrated circuitry to sense phase current, heat sink temperature and DC-bus voltage (option)
- Short circuit protection
- Over current protection
- Over voltage protection (option)
- Power supply protected against under voltage
- Interlock of top/bottom switch
- Isolation by transformer
- IEC 60068-1 (climate) 40/85/56
- UL recognized file no. 242581

| Absolute Maximum Ratings | | $T_a = 25^\circ\text{C}$ unless otherwise specified | |
|----------------------------------|--|---|-------------------|
| Symbol | Conditions | Values | Units |
| V_{S2} | unstabilized 24 V power supply | 30 | V |
| V_i | input signal voltage (high) | 15 + 0,3 | V |
| dv/dt | secondary to primary side | 75 | kV/ μs |
| V_{isolIO} | input / output (AC, rms, 2s) | 4000 | V |
| V_{isolPD} | partial discharge extinction voltage, rms, $Q_{\text{PD}} \leq 10$ pC; | 1500 | V |
| V_{isol12} | output 1 / output 2 (AC, rms, 2s) | 1500 | V |
| f_{sw} | switching frequency | 14 | kHz |
| f_{out} | output frequency for $I_{\text{peak}(1)} = I_C$ | 14 | kHz |
| $T_{\text{op}} (T_{\text{stg}})$ | operating / storage temperature | - 40 ... + 85 | $^\circ\text{C}$ |

| Characteristics | | $(T_a = 25^\circ\text{C})$ | | | |
|------------------------|--|--|------|------|------------------|
| Symbol | Conditions | min. | typ. | max. | Units |
| V_{S2} | supply voltage non stabilized | 13 | 24 | 30 | V |
| I_{S2} | $V_{S2} = 24$ V | $420 + 34 * f / \text{kHz} + 0,00015 * (I_{\text{AC}} / \text{A})^2$ | | | mA |
| $V_{\text{IT+}}$ | input threshold voltage (High) | 12,3 | | | V |
| $V_{\text{IT-}}$ | input threshold voltage (Low) | 4,6 | | | V |
| R_{IN} | input resistance | 10 | | | k Ω |
| C_{IN} | input capacitance | 1 | | | nF |
| $t_{\text{d(ON)IO}}$ | input-output turn-on propagation time | 1,3 | | | μs |
| $t_{\text{d(OFF)IO}}$ | input-output turn-off propagation time | 1,3 | | | μs |
| $t_{\text{pERRRESET}}$ | error memory reset time | 9 | | | μs |
| t_{TD} | top / bottom switch interlock time | 3 | | | μs |
| $I_{\text{analogOUT}}$ | max. 5mA; 8 V corresponds to 15 V supply voltage for external components | 500 | | | A |
| I_{s1out} | max. load current | 50 | | | mA |
| I_{TRIPSC} | over current trip level ($I_{\text{analog OUT}} = 10$ V) | 625 | | | A |
| T_{tp} | over temperature protection | 110 | 120 | | $^\circ\text{C}$ |
| U_{DCTRIP} | U_{DC} -protection ($U_{\text{analog OUT}} = 9$ V); () | 1200 | | | V |

For electrical and thermal design support please use SEMISEL.
Access to SEMISEL is via SEMIKRON website <http://www.semikron.com>.

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.



Case S33