

# SK60GAL123



SEMITOP<sup>®</sup> 2

## IGBT Module

SK60GAL123

SK60GAR123


Preliminary Data

### Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- N-channel homogeneous silicon structure (NPT-Non punch-through IGBT)
- High short circuit capability
- $V_{ce,sat}$  with positive coefficient
- Low tail current with low temperature dependence

### Typical Applications\*

- Switching (not for linear use)
- Inverter
- Switched mode power supplies
- UPS



GAL

GAR

Absolute Maximum Ratings		$T_s = 25^\circ\text{C}$ , unless otherwise specified	
Symbol	Conditions	Values	Units
<b>IGBT</b>			
$V_{CES}$	$T_j = 25^\circ\text{C}$	1200	V
$I_C$	$T_j = 125^\circ\text{C}$	$T_s = 25^\circ\text{C}$	58 A
		$T_s = 80^\circ\text{C}$	40 A
$I_{CRM}$	$I_{CRM} = 2 \times I_{Cnom}$	100	A
$V_{GES}$		$\pm 20$	V
$t_{psc}$	$V_{CC} = 600\text{ V}; V_{GE} \leq 20\text{ V}; T_j = 125^\circ\text{C}$ $V_{CES} < 1200\text{ V}$	10	$\mu\text{s}$

Inverse Diode		$T_s = 25^\circ\text{C}$ , unless otherwise specified	
Symbol	Conditions	Values	Units
$I_F$	$T_j = 150^\circ\text{C}$	$T_s = 25^\circ\text{C}$	33 A
		$T_s = 80^\circ\text{C}$	23 A
$I_{FRM}$	$I_{FRM} = 2 \times I_{Fnom}$		A
$I_{FSM}$	$t_p = 10\text{ ms}; \text{half sine wave } T_j = 150^\circ\text{C}$	110	A

Freewheeling Diode		$T_{case} = 25^\circ\text{C}$ , unless otherwise specified	
Symbol	Conditions	Values	Units
$I_F$	$T_j = 150^\circ\text{C}$	$T_{case} = 25^\circ\text{C}$	57 A
		$T_{case} = 80^\circ\text{C}$	38 A
$I_{FRM}$			A
$I_{FSM}$	$t_p = 10\text{ ms}; \text{half sine wave } T_j = 150^\circ\text{C}$	550	A

Module		$T_s = 25^\circ\text{C}$ , unless otherwise specified	
Symbol	Conditions	Values	Units
$I_{t(RMS)}$			A
$T_{vj}$		-40 ... +150	$^\circ\text{C}$
$T_{stg}$		-40 ... +125	$^\circ\text{C}$
$V_{isol}$	AC, 1 min.	2500	V

Characteristics		$T_s = 25^\circ\text{C}$ , unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
<b>IGBT</b>					
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 2\text{ mA}$	4,5	5,5	6,5	V
$I_{CES}$	$V_{GE} = 0\text{ V}, V_{CE} = V_{CES}$	$T_j = 25^\circ\text{C}$		0,3	mA
		$T_j = 125^\circ\text{C}$			mA
$I_{GES}$	$V_{CE} = 0\text{ V}, V_{GE} = 30\text{ V}$	$T_j = 25^\circ\text{C}$		300	nA
		$T_j = 125^\circ\text{C}$			nA
$V_{CE0}$		$T_j = 25^\circ\text{C}$	1,2		V
		$T_j = 125^\circ\text{C}$	1,2		V
$r_{CE}$	$V_{GE} = 15\text{ V}$	$T_j = 25^\circ\text{C}$	26		m $\Omega$
		$T_j = 125^\circ\text{C}$	38		m $\Omega$
$V_{CE(sat)}$	$I_{Cnom} = 50\text{ A}, V_{GE} = 15\text{ V}$	$T_j = 25^\circ\text{C}_{chiplev.}$	2,5	3	V
		$T_j = 125^\circ\text{C}_{chiplev.}$	3,1	3,7	V
$C_{ies}$	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	3,3		nF
$C_{oes}$			0,5		nF
$C_{res}$			0,22		nF
$Q_G$	$V_{GE} = 0 \dots 20\text{ V}$		285		nC
$t_{d(on)}$	$R_{Gon} = 22\ \Omega$	$V_{CC} = 600\text{ V}$ $I_C = 50\text{ A}$	70		ns
$t_r$			90		ns
$E_{on}$	$R_{Goff} = 22\ \Omega$	$T_j = 125^\circ\text{C}$ $V_{GE} = \pm 15\text{ V}$	9,9		mJ
$t_{d(off)}$			460		ns
$t_f$			30		ns
$E_{off}$			5,3		mJ
$R_{th(j-s)}$	per IGBT		0,6		K/W

# SK60GAL123



**SEMITOP® 2**

## IGBT Module

**SK60GAL123**

**SK60GAR123**


Preliminary Data

### Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- N-channel homogeneous silicon structure (NPT-Non punch-through IGBT)
- High short circuit capability
- $V_{ce,sat}$  with positive coefficient
- Low tail current with low temperature dependence

### Typical Applications\*

- Switching (not for linear use)
- Inverter
- Switched mode power supplies
- UPS







GAL




GAR

Characteristics					
Symbol	Conditions	min.	typ.	max.	Units
<b>Inverse Diode</b>					
$V_F = V_{EC}$	$I_{Fnom} = 10 \text{ A}; V_{GE} = 0 \text{ V}$	$T_j = 25 \text{ }^\circ\text{C}_{chiplev.}$	2	2,5	V
		$T_j = 125 \text{ }^\circ\text{C}_{chiplev.}$	1,8	2,3	V
$V_{F0}$		$T_j = 125 \text{ }^\circ\text{C}$	1	1,2	V
$r_F$		$T_j = 125 \text{ }^\circ\text{C}$	80		mΩ
$I_{RRM}$	$I_F = 10 \text{ A}$	$T_j = 125 \text{ }^\circ\text{C}$	12		A
$Q_{rr}$	$di/dt = -300 \text{ A}/\mu\text{s}$		1,8		μC
$E_{rr}$	$V_{CC} = 600\text{V}$		0,4		mJ
$R_{th(j-s)D}$	per diode			2,1	K/W
<b>Freewheeling Diode</b>					
$V_F = V_{EC}$	$I_{Fnom} = 50 \text{ A}; V_{GE} = 0 \text{ V}$	$T_j = 25 \text{ }^\circ\text{C}_{chiplev.}$	1	2,5	V
		$T_j = 125 \text{ }^\circ\text{C}_{chiplev.}$	1,8		V
$V_{F0}$		$T_j = 125 \text{ }^\circ\text{C}$	1	1,2	V
$r_F$		$T_j = 125 \text{ }^\circ\text{C}$	18	22	V
$I_{RRM}$	$I_F = 50 \text{ A}$	$T_j = 125 \text{ }^\circ\text{C}$	40		A
$Q_{rr}$	$di/dt = -800 \text{ A}/\mu\text{s}$		8		μC
$E_{rr}$	$V_R = 600\text{V}$		2,3		mJ
$R_{th(j-s)FD}$	per diode			0,9	K/W
$M_s$	to heat sink M1			2	Nm
w			21		g

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

\* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.






# SK60GAL123

UL recognized file

no. E 63 532



Case T18 (Suggested hole diameter, in the PCB, for solder pins and plastic mounting pins: 2mm)

