


SKD116/...-L140



SEMIPONT™ 6

3-Phase Bridge Rectifier + IGBT braking chopper

SKD116/...-L140

Data

Features

- Compact design
- Two screws mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- High surge currents
- Up to 1600V reverse voltage
- IGBT Trench4 inside; max $T_j=175^\circ\text{C}$
- CAL4F inside, max $T_j=175^\circ\text{C}$
- $I_{CM}/I_{FM} = 3 \times I_{C,nom}/I_{F,nom}$
- Rectifier diode, max $T_j=150^\circ\text{C}$


Typical Applications*

- DC drives
- Controlled filed rectifiers for DC motors
- Controlled battery charger

| | | |
|----------------|-------------------------|--|
| V_{RSM} V | V_{RRM}, V_{DRM} V | $I_D = 110$ A (maximum value for continuous operation) ($T_s = 85^\circ\text{C}$) |
| 1300 | 1200 | SKD 116/12-L140 |
| 1700 | 1600 | SKD116/16-L140 |

| Absolute Maximum Ratings | | $T_s = 25^\circ\text{C}$, unless otherwise specified | |
|---------------------------------|--|---|------------------|
| Symbol | Conditions | Values | Units |
| Bridge - Rectifier | | | |
| I_D | $T_s = 85^\circ\text{C}$; inductive load | 110 | A |
| I_{FSM}/I_{TSM} | $t_p = 10$ ms; $\sin 180^\circ$; T_{jmax} | 1050 | A |
| i^2t | $t_p = 10$ ms; $\sin 180^\circ$; T_{jmax} | 5500 | A ² s |
| IGBT - Chopper | | | |
| V_{CES}/V_{GES} | | 1200 / 20 | V |
| I_C | $T_s = 25$ (70) $^\circ\text{C}$ | 150 (120) | A |
| I_{CM} | $t_p = 1$ ms; $T_s = 25$ (70) $^\circ\text{C}$ | 520 | A |
| Freewheeling - CAL Diode | | | |
| V_{RRM} | | 1200 | V |
| I_F | $T_s = 25$ (70) $^\circ\text{C}$ | 130 (105) | A |
| I_{FM} | $t_p = 1$ ms; $T_s = 25$ (70) $^\circ\text{C}$ | 450 | A |
| T_{vj} | Diode & IGBT (Thyristor) | - 40 ... + 175 (-40...+ 125) | $^\circ\text{C}$ |
| T_{stg} | | - 40 ... + 125 | $^\circ\text{C}$ |
| T_{solder} | terminals, 10 s | 260 | $^\circ\text{C}$ |
| V_{isol} | a.c. (50) Hz, RMS 1 min. / 1 s | 3000 / 3600 | V |

| Characteristics | | $T_s = 25^\circ\text{C}$, unless otherwise specified | | | |
|-----------------------------------|--|---|-------------|-----------|----------------|
| Symbol | Conditions | min. | typ. | max. | Units |
| Diode - Rectifier | | | | | |
| V_{TO} / r_t | $T_j = 125^\circ\text{C}$ | | 0,8 / 7 | | V / m Ω |
| $R_{th(j-s)}$ | per diode | | | 1 | K/W |
| IGBT - Chopper | | | | | |
| $V_{CE(sat)}$ | $I_C = 140$ A, $T_j = 25^\circ\text{C}$; $V_{GE} = 15$ V | | 1,85 | 2,1 | V |
| $R_{th(j-s)}$ | per IGBT | | 0,38 | | K/W |
| $t_{d(on)} / t_r$ | valid for all values: $V_{CC} = 600$ V; $V_{GE} = 15$ V; | | 97 / 185 | | ns |
| $t_{d(off)} / t_f$ | $I_C = 140$ A; $T_j = 150^\circ\text{C}$; | | 443 / 82 | | ns |
| $E_{on} + E_{off}$ | $T_j = 150^\circ\text{C}$; $R_G = 4 \Omega$; inductive load | | 63,3 | | mJ |
| CAL - Diode - Freewheeling | | | | | |
| $V_{T(TO)} / r_t$ | $T_j = 150^\circ\text{C}$ | | 0,9 / 7,8 | 1,1 / 8,6 | V / m Ω |
| $R_{th(j-s)}$ | per diode | | 0,56 | | K/W |
| I_{RRM} | valid for all values: | | 30 | | A |
| Q_{rr} | $I_F = 140$ A; $V_R = - 600$ V; $di_F/dt = - 1700$ A/ μ s | | 9 | | μ C |
| E_{off} | $V_{GE} = 0$ V; $T_j = 150^\circ\text{C}$ | | 7,92 | | mJ |
| Temperature Sensor | | | | | |
| R_{TS} | $T = 25$ (100) $^\circ\text{C}$; | | 1000 (1670) | | Ω |
| Mechanical data | | | | | |
| M_S | mounting Torque | | 2,55 | 3,45 | Nm |






Fig. 1 Power dissipation per module vs. output current




Fig. 2 Surge overload current vs. time




Fig. 3 Forward characteristic of single rectifier diode




Fig. 4 Temperature sensor characteristic




Fig. 5 Typ. gate charge characteristic











Fig. 6 Output IGBT characteristics $I_c=f(V_{ce})$, $T_j=25^\circ\text{C}$




SKD116/...-L140

UL recognized
file no. E 63 532

Dimensions in mm



Case G 60



Case G 60

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.