

Micro Commercial Components


Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

BAS16WT MMBD4148WT

Features

- Power dissipation: 200mW (T_{amb}=25[°]C)
- Collector current:150mA



Marking: A2, KA2, KT1


Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

Electrical Characteristics @ 25°C Unless Otherwise Specified

| Reverse Voltage | V_R | 75V | I _R =100 μ A |
|--------------------|----------------|--------|---------------------------|
| Peak Forward | I _F | 150mA | |
| Current | | | |
| Maximum | | 0.715V | $I_{FM} = 1mA;$ |
| Instantaneous | V_{F} | 0.855 | $I_{FM} = 10 \text{mA};$ |
| Forward Voltage | | 1.0V | $I_{FM} = 50 \text{mA};$ |
| | | 1.25V | $I_{FM} = 150 \text{mA};$ |
| Maximum DC | | | |
| Reverse Current At | I_R | 1.0μΑ | V _R =75Volts |
| Rated DC Blocking | | | |
| Voltage | | | |
| Diode Capacitance | C_D | 2pF | Measured at 1.0MHz, |
| | | | $V_R=0V$ |
| Reverse Recovery | T_{rr} | 4ns | $I_F=I_R=10mA$ |
| Time | | | Irr=0.1I _R |

200mW Switching Diode



| DIMENSIONS | | | | | |
|------------|--------------|------|-------------|------|------|
| | INCHES | | MM | | |
| DIM | MIN | MAX | MIN | MAX | NOTE |
| Α | .071 | .087 | 1.80 | 2.20 | |
| В | .045 | .053 | 1.15 | 1.35 | |
| C | .079 | .087 | 2.00 | 2.20 | |
| D | .026 Nominal | | 0.65Nominal | | |
| Е | .047 | .055 | 1.20 | 1.40 | |
| F | .012 | .016 | .30 | .40 | |
| G | .000 | .004 | .000 | .100 | |
| Η | .035 | .039 | .90 | 1.00 | |
| ٦ | .004 | .010 | .100 | .250 | |
| K | .012 | .016 | .30 | .40 | |

Suggested Solder Pad Layout 0.70 1.90 1.90



Ordering Information

| Device | Packing |
|------------------|---------------------|
| (Part Number)-TP | Tape&Reel3Kpcs/Reel |

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.