

## Aluminum Capacitors + 105 °C, Miniature, Radial Lead




Fig.1 Component outline

QUICK REFERENCE DATA	
DESCRIPTION	VALUE
Nominal case size Ø D x L in mm	0.394" x 0.472" [10.0 x 12.0] to 0.709" x 1.575" [18.0 x 40.0]
Operating temperature	- 55 °C to + 105 °C
Rated capacitance range, C <sub>R</sub>	4.7 µF to 3300 µF
Tolerance on C <sub>R</sub>	- 10 %, + 50 %
Rated voltage range, U <sub>R</sub>	6.3 WVDC to 250 WVDC
Termination	2 and 3 radial leads and axial mount.
Life validation test at 105 °C	4000 hours (> 0.394" [10.0] diameter); 3000 hours (> 0.394" [10.0] diameter); Δ CAP ≤ 20 % from individual measurement. Δ ESR ≤ 1.15 x initial specified limit. Δ DCL ≤ 3 x initial specified limit.
Shelf life at 105 °C	500 hours: Δ CAP ≤ 10 % from initial measurement. Δ ESR ≤ 1.15 x initial specified limit. Δ DCL ≤ 2 x initial specified limit, (6.3 WVDC to 100 WVDC); ≤ 3 x initial specified limit, (150 WVDC to 250 WVDC).
DC leakage current at 25 °C	6.3 WVDC to 100 WVDC I = 0.03 √CV 150 WVDC to 250 WVDC I = 0.01 CV I in µA, C in µF, V in Volts

### FEATURES

- Original SMPS output capacitors
- Minimal ESR change
- High ripple current capability



### RIPLE CURRENT MULTIPLIERS

TEMPERATURE				
Ambient Temperature	Multipliers			
+ 105 °C	0.5			
+ 85 °C	1.0			
≤ + 75 °C	1.25			

FREQUENCY (Hz)				
WVDC	50 - 60	100 - 120	300 - 400	1K to 19K
0 - 75	0.60	0.70	0.75	0.80
76 - 100	0.40	0.55	0.70	0.80
101 - 250	0.25	0.35	0.45	0.65

### LOW TEMPERATURE PERFORMANCE

#### CAPACITANCE RATIO C - 55 °C/C + 25 °C MINIMUM AT 120 Hz

Maximum Capacitance Change	Voltage	Multiplier
	6.3 V - 100 V	0.75
	150 v - 250 V	0.70
Maximum Impedance Change	Voltage	Multiplier
	6.3 V - 100 V	2.5
	150 v - 250 V	2.0

#### ESL (TYPICAL VALUES AT 1 MHz TO 10 MHz)

Nominal diameter	0.394	0.512	0.630	0.709
Typical ESL (nH)	4.0	7.0	10.0	12.0


### DIMENSIONS in inches [millimeters]

CASE CODE	NOMINAL		STYLES 2 AND 4		STYLES 3 AND 5		LEAD SPACING		LEAD DIAMETER	
	D	L	D (max.)	L (max.)	D (max.)	L (max.)	S ± 0.024 [0.60]	T ± 0.020 [0.50]	Nominal	AWG
CC	0.394[10.0]	0.512[13.0]	0.413[10.5]	0.563[14.3]	0.413[10.5]	0.630[16.0]	0.197[5.0]	N/A	0.025[0.63]	22
CD	0.394[10.0]	0.630[16.0]	0.413[10.5]	0.669[17.0]	0.413[10.5]	0.740[18.8]	0.197[5.0]	N/A	0.025[0.63]	22
CG	0.394[10.0]	0.787[20.0]	0.413[10.5]	0.846[21.5]	0.413[10.5]	0.906[23.0]	0.197[5.0]	N/A	0.025[0.63]	22
DG	0.492[12.5]	0.787[20.0]	0.512[13.0]	0.846[21.5]	0.512[13.0]	0.906[23.0]	0.197[5.0]	0.098[2.5]	0.032[0.81]	20
DK	0.492[12.5]	0.984[25.0]	0.512[13.0]	1.043[26.5]	0.512[13.0]	1.142[29.0]	0.197[5.0]	0.098[2.5]	0.032[0.81]	20
DM	0.492[12.5]	1.043[26.5]	0.512[13.0]	1.102[28.0]	0.512[13.0]	1.161[29.5]	0.197[5.0]	0.098[2.5]	0.032[0.81]	20
DT	0.492[12.5]	1.319[33.5]	0.512[13.0]	1.346[34.2]	0.512[13.0]	1.417[36.0]	0.197[5.0]	0.098[2.5]	0.032[0.81]	20
DS	0.492[12.5]	1.673[42.5]	0.512[13.0]	1.720[43.7]	0.512[13.0]	1.791[45.5]	0.197[5.0]	0.098[2.5]	0.032[0.81]	20
EK	0.630[16.0]	0.984[25.0]	0.650[16.5]	1.031[26.2]	0.650[16.5]	1.098[27.9]	0.295[7.5]	0.150[3.8]	0.032[0.81]	20
EN	0.630[16.0]	1.260[32.0]	0.650[16.5]	1.319[33.5]	0.650[16.5]	1.417[36.0]	0.295[7.5]	0.150[3.8]	0.032[0.81]	20
ER	0.630[16.0]	1.417[36.0]	0.650[16.5]	1.476[37.5]	0.650[16.5]	1.575[40.0]	0.295[7.5]	0.150[3.8]	0.032[0.81]	20

DIMENSIONS in inches [millimeters]										
CASE CODE	NOMINAL		STYLES 2 AND 4		STYLES 3 AND 5		LEAD SPACING		LEAD DIAMETER	
	D	L	D (max.)	L (max.)	D (max.)	L (max.)	S ± 0.024 [0.60]	T ± 0.020 [0.50]	Nominal	AWG
EU	0.630 [16.0]	1.575 [40.0]	0.650 [16.5]	1.642 [41.7]	0.650 [16.5]	1.669 [42.4]	0.295 [7.5]	0.150 [3.8]	0.032 [0.81]	20
FR	0.709 [18.0]	1.417 [36.0]	0.728 [18.5]	1.476 [37.5]	0.728 [18.5]	1.575 [40.0]	0.295 [7.5]	0.150 [3.8]	0.032 [0.81]	20
FV	0.709 [18.0]	1.575 [40.0]	0.728 [18.5]	1.653 [42.0]	0.728 [18.5]	1.693 [43.0]	0.295 [7.5]	0.150 [3.8]	0.032 [0.81]	20


**TAPE AND REEL, SPECIFICATIONS TO EIA-468D in inches [millimeters]**

Formed Leads



DIMENSIONS in inches [millimeters] AND PACKAGING QUANTITIES		
CASE SIZE	F LEAD SPACING	STD. QTY/REEL
0.236 x 0.453 [6.0 x 11.0]	0.197 [5.0]	800
0.315 x 0.472 [8.0 x 12.0]	0.197 [5.0]	700

Unformed (Straight) Leads



DIMENSIONS in inches [millimeters] AND PACKAGING QUANTITIES		
CASE SIZE	F LEAD SPACING	STD. QTY/REEL
0.236 x 0.453 [6.0 x 11.0]	0.098 [2.5]	800
0.315 x 0.472 [8.0 x 12.0]	0.140 [3.5] <sup>(1)</sup>	700
0.394 x 0.512 [10.0 x 13.0]	0.197 [5.0]	500
0.394 x 0.630 [10.0 x 16.0]	0.197 [5.0]	500
0.394 x 0.787 [10.0 x 20.0]	0.197 [5.0]	500

 Note <sup>(1)</sup> Available as special order.

**DIMENSIONS** in inches [millimeters]

ITEM	CASE SIZE (Diameter x Length)				
	0.236 x 0.433 [6.0 x 11.0]	0.315 x 0.472 [8.0 x 12.0]	0.394 x 0.512 [10.0 x 13.0]	0.394 x 0.630 [10.0 x 16.0]	0.394 x 0.787 [10.0 x 20.0]
d - Lead-wire diameter	0.025 [0.63]	0.025 [0.63]	0.025 [0.63]	0.025 [0.63]	0.025 [0.63]
P - Pitch of component	0.500 [12.7]	0.500 [12.7]	0.500 [12.7]	0.500 [12.7]	0.500 [12.7]
P <sub>0</sub> - Feed hole pitch	0.500 [12.7]	0.500 [12.7]	0.500 [12.7]	0.500 [12.7]	0.500 [12.7]
F - Lead-to-lead distance	0.197 [5.0]	0.197 [5.0]	0.197 [5.0]	0.197 [5.0]	0.197 [5.0]
K - Clinch height	0.098 [2.5]	0.157 [4.0]	N/A	N/A	N/A
H - Height of component from tape center	0.728 [18.5]	0.787 [20.0]	0.906 [23.0]	0.906 [23.0]	0.906 [23.0]
H <sub>0</sub> - Lead-wire clinch height	0.630 [16.0]	0.630 [16.0]	N/A	N/A	N/A
W - Tape width	0.709 [18.0]	0.709 [18.0]	0.709 [18.0]	0.709 [18.0]	0.709 [18.0]
W <sub>0</sub> - Hold down tape width	0.591 [15.0]	0.591 [15.0]	0.591 [15.0]	0.591 [15.0]	0.591 [15.0]
D <sub>0</sub> - Feed hole diameter	0.157 [4.0]	0.157 [4.0]	0.157 [4.0]	0.157 [4.0]	0.157 [4.0]
f - Total tape thickness	0.028 [0.7]	0.028 [0.7]	0.028 [0.7]	0.028 [0.7]	0.028 [0.7]
L <sub>1</sub> - Maximum lead protrusion	0.118 [3.0]	0.118 [3.0]	0.118 [3.0]	0.118 [3.0]	0.118 [3.0]

**Note**

Positive leader is standard. Negative leader is available by special order.

**ORDERING EXAMPLE**

Electrolytic capacitor 672D series:

672D 336 F 100 DM 5 D

DESCRIPTION	
CODE	EXPLANATION
672D	product type
336	capacitance value (33 µF)
F	tolerance (F = -10 %/+ 50 %)
100	voltage rating at 105 °C (100 = 100 V)
DM	can size (see dimensions table)
5	sleeve and sealing (5 = polyester sleeve w/epoxy end seal)
D	packaging (D = bulk; straight leads)

**STANDARD RATINGS** in inches [millimeters]

CAPACITANCE (µF)	PART NUMBER	NOMINAL CASE SIZE D x L	Max. ESR AT + 25 °C (mΩ)		Max. RIPPLE AT + 85 °C (A) 20 kHz - 100 kHz	Max. IMPEDANCE AT + 25 °C (mΩ) 100 Hz
			120 Hz	20 kHz		
<b>6.3 WVDC AT 105 °C, SURGE = 9 V</b>						
150.0	672D157F6RCD5D	0.394 x 0.630 [10.0 x 16.0]	1.10	0.70	0.50	0.60
220.0	672D227F6RCG5D	0.394 x 0.787 [10.0 x 20.0]	0.75	0.40	0.70	0.33
1000.0	672D108F6REK5D	0.630 x 0.984 [16.0 x 25.0]	0.16	0.09	2.05	0.085
1500.0	672D158F6RET5D	0.630 x 1.319 [16.0 x 33.5]	0.105	0.06	2.90	0.055
3300.0	672D338F6RFV5D	0.709 x 1.575 [18.0 x 40.0]	0.075	0.045	3.40	0.045
<b>12 WVDC AT 105 °C, SURGE = 16 V</b>						
100.0	672D107F012CC5D	0.394 x 0.512 [10.0 x 13.0]	1.60	0.90	0.40	0.70
470.0	672D477F012CM5D	0.492 x 1.043 [12.5 x 26.5]	0.31	0.16	1.35	0.12
1000.0	672D108F012DS5D	0.492 x 1.673 [12.5 x 42.5]	0.15	0.08	2.35	0.06
2200.0	672D228F012FV5D	0.709 x 1.575 [18.0 x 40.0]	0.08	0.05	3.30	0.05
<b>15 WVDC AT 105 °C, SURGE = 20 V</b>						
100.0	672D107F015CD5D	0.394 x 0.630 [10.0 x 16.0]	1.35	0.70	0.50	0.50
470.0	672D477F015DT5D	0.492 x 1.319 [12.5 x 35.5]	0.25	0.12	1.75	0.11
1000.0	672D108F015ET5D	0.630 x 1.319 [16.0 x 33.5]	0.12	0.06	2.90	0.055
<b>20 WVDC AT 105 °C, SURGE = 30 V</b>						
100.0	672D107F020CG5D	0.394 x 0.787 [10.0 x 20.0]	1.25	0.40	0.70	0.35
470.0	672D477F020EK5D	0.630 x 0.984 [16.0 x 25.0]	0.24	0.09	2.00	0.085
1000.0	672D158F020FV5D	0.709 x 1.575 [18.0 x 40.0]	0.09	0.05	3.25	0.05



672D

Aluminum Capacitors  
+ 105 °C, Miniature, Radial Lead

Vishay Sprague

STANDARD RATINGS in inches [millimeters]						
CAPACITANCE ( $\mu$ F)	PART NUMBER	NOMINAL CASE SIZE D x L	Max. ESR AT + 25 °C (m $\Omega$ )		Max. RIPPLE AT + 85 °C (A) 20 kHz - 100 kHz	Max. IMPEDANCE AT + 25 °C (m $\Omega$ ) 100 Hz
			120 Hz	20 kHz		
<b>25 WVDC AT 105 °C, SURGE = 35 V</b>						
47.0	672D476F025CC5D	0.394 x 0.512 [10.0 x 13.0]	2.35	0.90	0.40	0.85
330.0	672D337F025DT5D	0.492 x 1.319 [12.5 x 33.5]	0.29	0.12	1.75	0.10
470.0	672D477F025DS5D	0.492 x 1.673 [12.5 x 42.5]	0.22	0.08	2.35	0.07
1200.0	672D128F025FV5D	0.709 x 1.575 [18.0 x 40.0]	0.10	0.05	3.20	0.055
<b>40 WVDC AT 105 °C, SURGE = 55 V</b>						
220.0	672D227F040EK5D	0.630 x 0.984 [16.0 x 25.0]	0.48	0.14	1.65	0.12
330.0	672D337F040ET5D	0.630 x 1.319 [16.0 x 33.5]	0.32	0.12	2.25	0.08
<b>50 WVDC AT 105 °C, SURGE = 75 V</b>						
100.0	672D107F050DT5D	0.492 x 1.319 [12.5 x 33.5]	0.80	0.26	1.15	0.22
150.0	672D157F050EK5D	0.630 x 0.984 [16.0 x 25.0]	0.55	0.22	1.30	0.18
220.0	672D277F050ET5D	0.630 x 1.319 [16.0 x 33.5]	0.40	0.15	1.85	0.12
470.0	672D477F050FV5D	0.709 x 1.575 [18.0 x 40.0]	0.25	0.09	2.40	0.095
<b>60 WVDC AT 105 °C, SURGE = 85 V</b>						
15.0	672D156F060CD5D	0.394 x 0.512 [10.0 x 13.0]	7.00	2.00	0.28	1.70
22.0	672D226F060CG5D	0.394 x 0.787 [10.0 x 20.0]	4.60	1.20	0.40	1.00
100.0	672D107F060EK5D	0.630 x 0.984 [16.0 x 25.0]	0.90	0.28	1.20	0.24
150.0	672D157F060ET5D	0.630 x 1.319 [16.0 x 33.5]	0.60	0.18	1.65	0.15
<b>75 WVDC AT 105 °C, SURGE = 100 V</b>						
12.0	672D126F075CD5D	0.394 x 0.512 [10.0 x 13.0]	8.50	2.20	0.26	1.75
120.0	672D127F075ET5D	0.630 x 1.319 [16.0 x 33.5]	0.68	0.18	1.50	0.16
<b>100 WVDC AT 105 °C, SURGE = 125 V</b>						
10.0	672D106F100CD5D	0.394 x 0.630 [10.0 x 16.0]	10.00	2.30	0.26	1.80
33.0	672D336F100DM5D	0.492 x 1.043 [12.5 x 26.5]	2.55	0.55	0.72	0.39
120.0	672D127F100ET5D	0.630 x 1.319 [16.0 x 33.5]	0.68	0.19	1.50	0.17
<b>200 WVDC AT 105 °C, SURGE = 250 V</b>						
4.7	672D475F200CG5D	0.394 x 0.787 [10.0 x 20.0]	22.50	1.95	0.31	1.75
15.0	672D156F200DT5D	0.492 x 1.319 [12.5 x 33.5]	7.00	0.58	0.76	0.55
47.0	672D476F200FV5D	0.709 x 1.575 [18.0 x 40.0]	2.30	0.18	1.90	0.165
<b>250 WVDC AT 105 °C, SURGE = 300 V</b>						
10.0	672D106F250DT5D	0.492 x 1.319 [12.5 x 33.5]	12.00	1.50	0.48	1.60

ORIGINAL RATINGS		
CAPACITANCE ( $\mu$ F)	CASE CODE	PART NUMBER
<b>6.3 WVDC AT 105 °C, SURGE = 9 V</b>		
150.0	CD	672D157H6R3CD5C
220.0	CG	672D227H6R3CG5C
680.0	DM	672D687H6R3DM5C
1000.0	EK	672D108H6R3EK5C
1200.0	DS	672D158H6R3ET5C
3300.0	FV	672D338H6R3FV5C
<b>7.5 WVDC AT 105 °C, SURGE = 10 V</b>		
100.0	CC	672D107H7R5CC5C
150.0	CD	672D157H7R5CD5C
680.0	DT	672D687H7R5DT5C
1000.0	ET	672D108H7R5ET5C
2700.0	FV	672D278H7R5FV5C

**Notes**

(1) Capacitance Tolerance Code H, - 10 %, + 100 %; Lead Code C, cut leads. C Lead = Negative Lead: 0.281" [7.1 mm],  $\pm$  0.062" [1.6 mm]; Positive Lead: 0.375" [9.5 mm],  $\pm$  0.062" [1.6 mm]. D Lead = 1.0" [25.4 mm] minimum.

**ORIGINAL RATINGS**

CAPACITANCE ( $\mu\text{F}$ )	CASE CODE	PART NUMBER
<b>12 WVDC AT 105 °C, SURGE = 16 V</b>		
100.0	CC	672D107H012CC5C
150.0	CG	672D157H012CG5C
470.0	DM	672D477H012DM5C
680.0	DT	672D687H012DT5C
1000.0	DS	672D108H012DS5C
2200.0	FV	672D228H012FV5C
<b>15 WVDC AT 105 °C, SURGE = 20 V</b>		
100.0	CD	672D107H015CD5C
150.0	CG	672D157H015CG5C
470.0	DT	672D477H015DT5C
680.0	EK	672D687H015EK5C
820.0	DS	672D827H015DS5C
1000.0 <sup>(1)</sup>	ET	672D108H015ET5C
1800.0	FV	672D188H015FV5C
<b>20 WVDC AT 105 °C, SURGE = 30 V</b>		
68.0	CD	672D868H020CD5C
100.0	CG	672D107H020CG5C
330.0	DM	672D337H020DM5C
470.0	EK	672D477H020EK5C
560.0	DS	672D567H020DS5C
680.0	ET	672D687H020ET5C
1500.0	FV	672D158H020FV5C
<b>25 WVDC AT 105 °C, SURGE = 35 V</b>		
47.0	CC	672D476H025CC5C
68.0	CD	672D686H025CD5C
330.0	DT	672D337H025DT5C
470.0	DS	672D477H025DS5C
680.0	EU	672D687H025EU5C
1200.0	FV	672D128H025FV5C
<b>40 WVDC AT 105 °C, SURGE = 55 V</b>		
47.0	CD	672D476H040CD5C
220.0	EK	672D227H040EK5C
330.0	ET	672D337H040ET5C
390.0	DS	672D397H040DS5C
820.0	FV	672D827H040FV5C
<b>50 WVDC AT 105 °C, SURGE = 75 V</b>		
22.0	CD	672D226H050CD5C
100.0	DT	672D107H050DT5C
150.0	EK	672D157H050EK5C
180.0	DS	672D187H050DS5C
220.0	ET	672D227H050ET5C
470.0	FV	672D477H050FV5C
<b>60 WVDC AT 105 °C, SURGE = 85 V</b>		
15.0	CD	672D156H060CD5C
22.0	CG	672D226H060CG5C
68.0 <sup>(1)</sup>	DM	672D686H060DM5C
100.0	EK	672D107H060EK5C
120.0	DS	672D127H060DS5C
150.0	ET	672D157H060ET5C
390.0	FV	672D397H060FV5C

**Notes**

<sup>(1)</sup> Capacitance Tolerance Code H, - 10 %, + 100 %; Lead Code C, cut leads. C Lead = Negative Lead: 0.281" [7.1 mm],  $\pm 0.062"$  [1.6 mm]; Positive Lead: 0.375" [9.5 mm],  $\pm 0.062"$  [1.6 mm]. D Lead = 1.0" [25.4 mm] minimum.



672D

Aluminum Capacitors  
+ 105 °C, Miniature, Radial Lead

Vishay Sprague

ORIGINAL RATINGS		
CAPACITANCE ( $\mu$ F)	CASE CODE	PART NUMBER
75 WVDC AT 105 °C, SURGE = 100 V		
12.0	CD	672D126H075CD5C
18.0	CG	672D186H075CG5C
82.0	EK	672D826H075EK5C
120.0	ET	672D127H075ET5C
270.0	FV	672D277H075FV5C
100 WVDC AT 105 °C, SURGE = 125 V		
8.2	CC	672D825H100CC5C
10.0	CD	672D106H100CD5C
33.0	DM	672D336H100DM5C
68.0	EK	672D686H100EK5C
120.0	ET	672D127H100ET5C
180.0	FV	672D187H100FV5C
150 WVDC AT 105 °C, SURGE = 200 V		
6.8	CG	672D685H150CG5C
22.0	DT	672D226H150DT5C
39.0	ET	672D396H150ET5C
68.0	FV	672D686H150FV5C
200 WVDC AT 105 °C, SURGE = 250 V		
4.7	CG	672D475H200CG5C
15.0	DT	672D156H200DT5C
27.0	ET	672D276H200ET5C
47.0	FV	672D476H200FV5C
250 WVDC AT 105 °C, SURGE = 300 V		
8.2	DM	672D825H250DM5C
10.0	DT	672D106H250DT5C
22.0	ET	672D226H250ET5C
39.0	FV	672D396H250FV5C

**Notes**

<sup>(1)</sup> Capacitance Tolerance Code H, - 10 %, + 100 %; Lead Code C, cut leads. C Lead = Negative Lead: 0.281" [7.1 mm],  $\pm$  0.062" [1.6 mm]; Positive Lead: 0.375" [9.5 mm],  $\pm$  0.062" [1.6 mm]. D Lead = 1.0" [25.4 mm] minimum.



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.