


10-Watt Lednium SMD Series (120° Viewing Angle)

OVTL09LGAX

- Revolutionary 3-dimensional packaged LED source
- Robust energy-efficient design with long operating life
- Low thermal resistance
- Exceptional spatial uniformity
- Optional optics to suit application
- Available in amber, blue, green, red, white and multi-colored





The **OVTL09LGAX** surface mount series provides a 10-Watt energy-efficient 3-dimensional packaged LED source that offers high luminance (up to 330 lumens), low thermal resistance and a long operating lifespan. The device offers a 120° viewing angle and is available in amber, blue, green, red, white and multi-colored. Optional optics are offered to suit application. Please contact Optek for additional information.

Applications

- Automotive exterior and interior lighting
- Architectural lighting
- Electronic signs and signals

Part Number	Viewing Angle	Emitted Color	Typical Luminous Flux (lm)	Typical On-Axis Intensity (cd)	Lens Color
OVTL09LGAA	120°	Amber	330	67	Water Clear
OVTL09LGAB	120°	Blue	60	19	Water Clear
OVTL09LGAG	120°	Green	290	100	Water Clear
OVTL09LGAR	120°	Red	247	75	Water Clear
OVTL09LGAW	120°	White	250	70	Water Clear
OVTL09LGAM	120°	Red/Green/Blue	221	68	Water Clear



OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

10-Watt Lednium Surface Mount Series

OVTL09LGAX



Absolute Maximum Ratings

DC Forward Current	1.05 A
Peak Pulsed Forward Current ¹	3 A
Reverse Voltage	15 V
Maximum Allowable Junction Temperature ²	130 °C
Storage and Operating Temperature	-50 ° ~ +80 ° C

Notes:

1. Pulse width 1 ms maximum, duty cycle 1/16.
2. Thermal resistance junction to board (T_{JB}) is 5 ° C/W.

Electrical Characteristics ($I_F = 600 \text{ mA}$, $T_J = 25^\circ \text{C}$)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS
V_F	Forward Voltage (Amber)	6.3	6.4	6.5	V
	Forward Voltage (Blue)	8.9	9.1	9.25	V
	Forward Voltage (Green)	9.75	9.9	10.1	V
	Forward Voltage (Red)	6.0	6.1	6.2	V
	Forward Voltage (Red/Green/Blue)	8.4	8.6	8.8	V
	Forward Voltage (White)	8.9	9.1	9.25	V
$2 \Theta_{1/2}$	V_F Temperature Co-efficient (Amber, Red)	----	-6.0	----	mV/°C
	V_F Temperature Co-efficient (White, Blue)	----	-4.8	----	mV/°C
	V_F Temperature Co-efficient (Green)	----	-5.0	----	mV/°C
$2 \Theta_{1/2}$	50% Power Angle	----	120	----	deg


Optical Characteristics ($I_F = 1.05 \text{ A}$, $T_J = 25^\circ \text{C}$, $2 \Theta_{1/2} = 120^\circ$)

COLOR	DOMINANT WAVELENGTH			SPECTRAL FULL-WIDTH-HALF-MAXIMUM	DOMINANT WAVELENGTH TEMPERATURE DEPENDENCE
	MIN	TYP	MAX		
Amber	594	595	596	16 nm	0.08 nm/°C
Blue	466	467	468	24 nm	0.05 nm/°C
Green	523	524	526	40 nm	0.04 nm/°C
Red	623	624	625	18 nm	0.05 nm/°C
White	N/A	N/A	N/A	N/A	N/A


OPTEK's Lednium Series Solid State Lighting products package the highest quality LED chips. Typically, the lumen output of these chips can be as high as 70% after 50,000 hours of operation. This prediction is based on specific test results and on tests on similar materials, and relies on strict observation of the design limits and ratings included in this data sheet.

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

CIE Chromaticity Diagram




Spatial Intensity Distribution




Normalized Spectral Intensity vs Angular Displacement

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


Typical Electro-Optical Characteristics Curves




Wavelength Characteristics




Wavelength Characteristics




Junction Temperature Characteristics



Forward Current Characteristics



Derating Curves - Blue, Green and White LEDs





Derating Curves - Amber and Red LEDs

OPTeK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

10-Watt Lednium Surface Mount Series

OVTL09LGAX

OPTEK Lednium Turtle Markings



Packaging: 25 pieces per tray

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.