

# XALD01

dark grey empty enclosure lid with light grey base - 1 cut-out



## Main

|                             |   |
|-----------------------------|---|
| Range of product            | Harmony XALD  |
| Product or component type   | Empty control station   |
| Device short name           | XALD  |
| Product destination         | For XB5 Ø 22 mm control and signalling units  |
| Number of cut-out           | 1 cut-out   |
| Colour of base of enclosure | Light grey RAL 7035   |
| Colour of cover             | Dark grey RAL 7016  |
| Material                    | Polycarbonate   |
| Cable entry                 | 1 knock-out for cable entry, clamping capacity: <= 14 mm<br>2 knock-outs for Pg 13 cable gland and ISO M20, clamping capacity: <= 12 mm |
| IP degree of protection     | IP65 conforming to IEC 60529  |

## Complementary

|                                    |                                      |
|------------------------------------|--------------------------------------|
| Assembly style                     | For customer assembly                |
| Number of vertical rows            | 1                                    |
| Product weight                     | 0.136 kg                             |
| Resistance to high pressure washer | 7000000 Pa at 55 °C, distance: 0.1 m |
| Mounting of block                  | Front mounting<br>Rear mounting      |
| Main group                         | 1 cut-out                            |
| Group of product                   | Standard grey                        |

## Environment

|  |   |
|--|---|
| Protective treatment                       | TH  |
| Ambient air temperature for storage        | -40...70 °C   |
| Ambient air temperature for operation      | -25...70 °C   |
| Class of protection against electric shock | Class II conforming to IEC 60536  |
| NEMA degree of protection                  | NEMA 13<br>NEMA 4X  |
| IK degree of protection                    | IK03 conforming to EN 50102   |
| Standards                                  | CSA C22-2 No 14<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>JIS C 4520<br>UL 508 |
| RoHS EUR status                            | Compliant   |
| RoHS EUR conformity date                   | 0810  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.