



Main

Range of product	OsiSense XM
Product or component type	Electronic pressure sensors
Pressure switch type of operation	Regulation between 2 thresholds
Pressure sensor name	XMLF
Pressure sensor size	-1 bar
Fluid connection type	G 1/4 (female) conforming to ISO 228
Controlled fluid	Sea water (-15...80 °C) Hydraulic oil (-15...80 °C) Fresh water (-15...80 °C) Corrosive fluid (-15...80 °C) Air (-15...80 °C)
Type of output signal	Analogue + discrete
Analogue output function	4...20 mA
Discrete output type	Solid state PNP or NPN programmable, 1 NO or 1 NC programmable
Electrical connection	4 pins male connector M12
Product specific application	-
Adjustable range of switching point on rising pressure	-0.97...-0.05 bar
Adjustable range of switching point on falling pressure	-1...-0.08 bar
Destruction pressure	5 bar
Type of installation	Control circuit
Scale type	Adjustable differential scale
Maximum switching current	200 mA
[Us] rated supply voltage	24 V DC, voltage limits: 17...33 V
Materials in contact with fluid	FPM (Viton) Stainless steel type AISI 303

Complementary

Setting	External setting
Possible differential minimum at low setting	0.03 bar
Possible differential minimum at high setting	0.03 bar
Possible differential maximum at low setting	0.95 bar
Maximum permissible accidental pressure	3 bar
Local display	With
Protection type	Connection faults Overload protection Reverse polarity Short-circuit protection
Current consumption	80 mA
Operating rate in Hz	<= 50 Hz
Drift of the sensitivity	< +/- 0.03 % of msrg range /°C
Drift of the zero point	< +/- 0.1 % of msrg range /°C
Time delay range	0...50 s in steps of 1 second

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Response time on output	5...500 ms, in steps of 1 ms
Mechanical durability	>= 10000000 cycles
Display response time type	Fast Normal Slow
CAD overall depth	58 mm
CAD overall height	113 mm
CAD overall width	46 mm
Product weight	0.48 kg
Surge withstand	0.5 kV DC
Measurement accuracy	<= 0.6 % of the measuring range
Repeat accuracy	<= 0.5 %

Environment

Operating position	Any position
Standards	CE EN 50081 EN 50082 EN 61000-4-11 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-8 EN 61000-6-2 EN/IEC 60947-1 EN/IEC 60947-5-1
Product certifications	CSA UL
Ambient air temperature for operation	-25...80 °C
Vibration resistance	5 gn (f = 25...200 Hz) conforming to IEC 68-2-6 35 gn (f = 60...2000 Hz) conforming to IEC 68-2-6
Protective treatment	TC
Shock resistance	50 gn conforming to IEC 68-2-27
Resistance to fast transients	2 kV conforming to EN 61000-4-4
IP degree of protection	IP67 conforming to EN/IEC 60529
NEMA degree of protection	NEMA 12 NEMA 13 NEMA 4 NEMA 6
Resistance to electrostatic discharge	8 kV (in air) conforming to EN 61000-4-2 4 kV (on contact) conforming to EN 61000-4-2
Resistance to electromagnetic fields	10 V/m conforming to EN 61000-4-3
Resistance to conducted disturbances, induced by radio frequency fields	10 V conforming to EN 61000-4-6

Offer Sustainability

Sustainable offer status	Not Green Premium product
ROHS	Compliant - since 0627 - download declaration of conformity
REACH	Reference not containing SVHC above the threshold