



Main

Range of product	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Motor control Ohmic load
Utilisation category	AC-1 AC-3

Complementary

Protective cover	With
Motor power kW	100 kW at 220...230 V AC 50/60 Hz 160 kW at 1000 V AC 50/60 Hz 160 kW at 380...400 V AC 50/60 Hz 180 kW at 415 V AC 50/60 Hz 200 kW at 440 V AC 50/60 Hz 200 kW at 500 V AC 50/60 Hz 220 kW at 660...690 V AC 50/60 Hz
Motor power hp	100 hp at 230/240 V AC 60 Hz conforming to CSA 100 hp at 230/240 V AC 60 Hz conforming to UL 200 hp at 460/480 V AC 60 Hz conforming to CSA 200 hp at 460/480 V AC 60 Hz conforming to UL 250 hp at 575/600 V AC 60 Hz conforming to CSA 250 hp at 575/600 V AC 60 Hz conforming to UL 75 hp at 200/208 V AC 60 Hz conforming to CSA 75 hp at 200/208 V AC 60 Hz conforming to UL
Mounting mode	Fixed
Mounting support	Plate Rail
Tightening torque	35 N.m power circuit: - on bars 35 N.m power circuit: - on lug - cable 240 mm ²
[Ue] rated operational voltage	<= 1000 V AC 16 Hz 2/3...200 Hz for power circuit
[Ith] conventional free air thermal current	400 A at <= 40 °C for power circuit
Irms rated making capacity	3300 A at <= 1000 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	2640 A at <= 1000 V for power circuit conforming to IEC 60947-4-1
Permissible short-time rating	1300 A (<= 40 °C) - short time current duration: 1 min - for power circuit 1800 A (<= 40 °C) - short time current duration: 30 s - for power circuit 2650 A (<= 40 °C) - short time current duration: 10 s - for power circuit 750 A (<= 40 °C) - short time current duration: 10 min - for power circuit 900 A (<= 40 °C) - short time current duration: 3 min - for power circuit
Associated fuse rating	400 A aM at <= 440 V for power circuit 500 A gG at <= 440 V for power circuit
Average impedance	0.28 mOhm at 50 Hz - Ith 400 A for power circuit
Power dissipation per pole	31 W AC-3 - Ith 400 A 44 W AC-1 - Ith 400 A
Mechanical durability	10000000 cycles
Height	206 mm
Width	213 mm
Depth	219 mm
Product weight	8.6 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Poles description	3P
Pole contact composition	3 NO
[Ie] rated operational current	330 A (<= 55 °C) AC network AC-3 for power circuit 400 A (<= 40 °C) AC network AC-1 for power circuit
Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JEM 1038
Product certifications	BV CCC CSA DNV (Det Norske Veritas) GL LROS (Lloyds register of shipping) RINA RMR0S UL
IP degree of protection	IP2x conforming to IEC 60529 IP2x conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating in temperature
Shock resistance	15 gn contactor closed 6 gn contactor opened
Vibration resistance	2 gn contactor opened 5...300 Hz 5 gn contactor closed 5...300 Hz
Connections - terminals	Bars power circuit: 2 Connector power circuit: 1 cable 240 mm ² Lug power circuit: 1 cable 240 mm ²