

# XACB911

boot with circlip XAC-B - for booted operator -  
polychloroprene - 4 mm

## Main

|                                       |                   |
|---------------------------------------|-------------------|
| Range of product                      | Harmony XAC       |
| Accessory / separate part designation | Boot with circlip |
| Accessory / separate part type        | Boot              |
| Accessory / separate part category    | Separate parts    |
| Product compatibility                 | XACB91.           |
| Accessory / separate part destination | Booted operator   |
| Operating travel                      | 4 mm              |
| Material                              | Polychloroprene   |
| Sale per indivisible quantity         | 10                |

## Complementary

|                |          |
|----------------|----------|
| Product weight | 0.002 kg |
|----------------|----------|

## Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...70 °C |
|---------------------------------------|-------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.