

Main

Range of product	C120 C60 DPN
Device short name	MX + OF
Signal contacts composition	1 NO/NC

Complementary

Mounting mode	Fixed
Wire stripping length	9 mm
Tightening torque	1 N.m
Auxiliary connection terminal	Clamp terminal 1 cable(s) flexible 2.5 mm ² 1 cable(s) rigid 2.5 mm ² 2 cable(s) flexible 1.5 mm ² 2 cable(s) rigid 1.5 mm ²
Control circuit voltage	48 V AC 50/60 Hz 48 V DC
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Depth	68 mm
Height	82.5 mm
Width	18 mm

Environment

Product certifications	ASEFA ASTA KEMA LCIE
Standards	IEC 60947-2
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	0.95 % (55 °C)
Tropicalisation	2 conforming to IEC 60947-2
RoHS EUR conformity date	0743
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.