



Main

Range of product	Terminal blocks
Product or component type	Terminal block
Technology type	Screw technology
Terminal block type	Miniature passthrough
Fixing mode	Clip-on mounting on 15 mm symmetrical DIN rail
Nominal cross section	4 mm ²
Length	28.5 mm
Colour	Grey
Number of points	2
Sale per indivisible quantity	100

Complementary

Width	6 mm
Height	32 mm on 15 mm symmetrical DIN rail
Cable cross section	0.5...2.5 mm ² , flexible with cable end 0.5...4 mm ² , flexible without cable end 0.5...6 mm ² , solid
Tightening torque	0.5...0.7 N.m, M3 conforming to EN 60999 0.5...0.7 N.m, M3 conforming to IEC 60974-1
[Ue] rated operational voltage	150 V , 22...14 AWG UL 275 V conforming to ATEX Exe II Ex II 2 GD 500 V conforming to EN/IEC 60947-7-1 500 V AC conforming to VDE group C 500 V AC/DC conforming to UTE category C 600 V DC conforming to VDE group C
[Ie] rated operational current	10 A, 22...14 AWG UL 21...27 A conforming to ATEX Exe II Ex II 2 GD 3...34 A conforming to EN/IEC 60947-7-1 34 A conforming to VDE group C
Material	Copper or brass (commoning link) Polyamide 6.6 (insulating case) Zinc chromed steel (connector and screw)
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	Conforming to IEC 60093 Conforming to VDE 0303-T30
Surface resistance	10 GOhm conforming to IEC 60093 10 GOhm conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame retardance	V0, thickness 0.8 mm conforming to UL 94
Product weight	5.5 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Dielectric test voltage	6 kV conforming to EN/IEC 60947-7-1
Product certifications	ASEV ATEX CSA CSA-Ex LR UL UL-Aex UL-Ex
Dielectric strength	80 kV conforming to IEC 60243-1 80 kV conforming to VDE 0303-T21
Ambient air temperature for operation	-40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21