

ATV31HU30M3XA

variable speed drive ATV31 - 3kW - 240V 3-phase supply - IP20

Main

Range of product	Altivar
Product or component type	Variable speed drive
Product specific application	Simple machine
Component name	ATV31
Assembly style	With heat sink
Variant	With drive order potentiometer
EMC filter	Without EMC filter
[Us] rated supply voltage	200...240 V - 5...5 %
Supply frequency	50...60 Hz - 5...5 %
Network number of phases	3 phases
Motor power kW	3 kW 4 kHz
Motor power hp	4 kHz
Line current	16.6 A 240 V 19.1 A 200 V 1 kA
Apparent power	6.6 kVA
Prospective line I _{sc}	1 kA
Nominal output current	13.7 A 4 kHz
Maximum transient current	20.6 A 60 s
Power dissipation in W	146 W at nominal load
Asynchronous motor control profile	Factory set : constant torque Sensorless flux vector control with PWM type motor control signal

Complementary

Product destination	Asynchronous motors
Supply voltage limits	170...264 V
Network frequency limits	47.5...63 Hz
Speed drive output frequency	0.5...500 Hz
Nominal switching frequency	4 kHz
Switching frequency	2...16 kHz adjustable
Speed range	1...50
Transient overtorque	150...170 % of nominal motor torque
Braking torque	100 % with braking resistor continuously 150 % without braking resistor ≤ 150 % with braking resistor 60 s
Regulation loop	Frequency PI regulator
Motor slip compensation	Adjustable Automatic whatever the load Suppressable
Output voltage	≤ power supply voltage
Electrical connection	Terminal 2.5 mm ² AWG 14 AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6 Terminal 2.5 mm ² AWG 14 L1, L2, L3, U, V, W, PA, PB, PA+, PC/-
Tightening torque	0.6 N.m AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6 0.8 N.m L1, L2, L3, U, V, W, PA, PB, PA+, PC/-
Insulation	Electrical between power and control

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Supply	Internal supply for logic inputs $19...30\text{ V} \leq 100\text{ mA}$ overload and short-circuit protection Internal supply for reference potentiometer ($2.2\text{ to }10\text{ k}\Omega$) $10...10.8\text{ V} \leq 10\text{ mA}$ overload and short-circuit protection
Analogue input number	4
Analogue input type	Configurable current AI3 $0...20\text{ mA}$ $250\text{ }\Omega$ Configurable voltage AI1 $0...10\text{ V}$ 30 V max $30000\text{ }\Omega$ Configurable voltage AI2 $\pm 10\text{ V}$ 30 V max $30000\text{ }\Omega$ Potentiometer reference AIP 8 ms 10 bits $\pm 4.3\%$ $\pm 0.2\%$
Sampling duration	4 ms LI1...LI6 discrete 8 ms AI1, AI2, AI3 analog
Response time	8 ms discrete R1A, R1B, R1C, R2A, R2B 8 ms analog AOV, AOC
Linearity error	$\pm 0.2\%$ output
Analogue output number	2
Analogue output type	Configurable current AOC $0...20\text{ mA}$ $800\text{ }\Omega$ 8 bits Configurable voltage AOV $0...10\text{ V}$ $470\text{ }\Omega$ 8 bits
Discrete input logic	Logic input not wired LI1...LI4 $< 13\text{ V}$ Negative logic (source) LI1...LI6 $> 19\text{ V}$ Positive logic (source) LI1...LI6 $< 5\text{ V}$ $> 11\text{ V}$
Discrete output number	2
Discrete output type	Configurable relay logic R1A, R1B, R1C $1\text{ NO} + 1\text{ NC}$ 100000 cycles Configurable relay logic R2A, R2B NC 100000 cycles
Minimum switching current	10 mA 5 V DC R1-R2
Maximum switching current	2 A 250 V AC inductive $\cos\phi = 0.4$ 7 ms R1-R2 2 A 30 V DC inductive $\cos\phi = 0.4$ 7 ms R1-R2 5 A 250 V AC resistive $\cos\phi = 1$ 0 ms R1-R2 5 A 30 V DC resistive $\cos\phi = 1$ 0 ms R1-R2
Discrete input number	6
Discrete input type	Programmable LI1...LI6 24 V $0...100\text{ mA}$ PLC $3500\text{ }\Omega$ Programmable LI1...LI6 24 V $0...100\text{ mA}$ PLC $3500\text{ }\Omega$
Acceleration and deceleration ramps	S, U or customized Linear adjustable separately from 0.1 to 999.9 s
Braking to standstill	By DC injection
Protection type	Input phase breaks drive Line supply overvoltage and undervoltage safety circuits drive Line supply phase loss safety function, for three phases supply drive Motor phase breaks drive Overcurrent between output phases and earth (on power up only) drive Overheating protection drive Short-circuit between motor phases drive Thermal protection motor
Insulation resistance	$\geq 500\text{ M}\Omega$ 500 V DC for 1 minute
Display type	1 LED red drive voltage Four 7-segment display units CANopen bus status
Time constant	5 ms for reference change
Frequency resolution	$0.1...100\text{ Hz}$ analog input 0.1 Hz display unit
Type of connector	1 RJ45 Modbus 1 RJ45 CANopen via VW3 CANTAP2 adaptor
Physical interface	RS485 multidrop serial link Modbus RS485 multidrop serial link CANopen via VW3 CANTAP2 adaptor
Transmission frame	RTU Modbus RTU CANopen via VW3 CANTAP2 adaptor
Transmission rate	$10, 20, 50, 125, 250, 500\text{ kbps}$ or 1 Mbps CANopen via VW3 CANTAP2 adaptor $4800, 9600$ or 19200 bps Modbus
Number of addresses	$1...127$ CANopen via VW3 CANTAP2 adaptor $1...247$ Modbus
Number of drive	31 Modbus 127 CANopen via VW3 CANTAP2 adaptor
Marking	CE
Operating position	Vertical $\pm 10\text{ degree}$
Product weight	2.9 kg

Environment

Dielectric strength	2040 V DC between earth and power terminals 2880 V AC between control and power terminals
Electromagnetic compatibility	1.2/50 μ s - 8/20 μ s surge immunity test level 3 IEC 61000-4-5 Electrical fast transient/burst immunity test level 4 IEC 61000-4-4 Electrostatic discharge immunity test level 3 IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 IEC 61000-4-3
Standards	EN 50178
Product certifications	C-Tick CSA N998 UL
IP degree of protection	IP20 on upper part without cover plate IP21 on connection terminals IP31 on upper part IP41 on upper part
Pollution degree	2
Protective treatment	TC
Vibration resistance	1 gn 13...150 Hz EN/IEC 60068-2-6 1.5 mm 3...13 Hz EN/IEC 60068-2-6
Shock resistance	15 gn 11 ms EN/IEC 60068-2-27
Relative humidity	5...95 % without condensation IEC 60068-2-3 5...95 % without dripping water IEC 60068-2-3
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...50 °C without derating with protective cover on top of the drive -10...60 °C with derating factor without protective cover on top of the drive
Operating altitude	\leq 1000 m without derating \geq 1000 m with current derating 1 % per 100 m
RoHS EUR conformity date	0723
RoHS EUR status	Compliant