VW3A58501

line choke - 2 mH - 25 A - 1 phase - 45 W - for variable speed drive

Main	
Product or component type	Line choke
Number of phases	1 phase
Range compatibility	Altivar 61 Altivar 71
Product specific application	Reduction of current harmonics
Value of inductance	2 mH
[In] rated current	25 A
Product compatibility	ATV61HU40M3 ATV71HU40M3
Thermal losses	45 W
Electrical connection	Terminal 16 mm² / AWG 4, 1.21.4 N.m

Complementary

Power supply frequency	5060 Hz	
Max current	1.65 x nominal current for 60 s	
Voltage drop at rated load	35 %	
Electrical insulation class	Class F	
Clearance distance	5.5 mm conforming to IEC 60664	
Leakage distance	11.5 mm conforming to IEC 60664	
Product weight	3.5 kg	
Width	133 mm	
Height	150 mm	
Depth	95 mm	

Environment

Standards	EN 50178
	IEC 60076 (with HD398)
	VDE 0160 level 1
IP degree of protection	IP00 (choke)
	IP20 (terminals)
Environmental characteristic	3B1 conforming to IEC 721-3-3
	3C2 conforming to IEC 721-3-3
	3S1 conforming to IEC 721-3-3
Pollution degree	2 conforming to EN 50178
Vibration resistance	1 gn (f = 13200 Hz) conforming to IEC 60068-2-6
	1.5 mm peak to peak (f = 313 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Relative humidity	<= 95 %
Ambient air temperature for operation	> 45< 55 °C with current derating of 2 % per °C
	045 °C without current derating
Ambient air temperature for storage	-2570 °C
Operating altitude	<= 1000 m without derating
	10003000 m with current derating 1 % per 100 m
RoHS EUR status	Compliant
RoHS EUR conformity date	0802