

Product data sheet

Characteristics

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

XCSD3702N12

safety limit switch - metal - roller plunger - 2NC
+1NO - 1 entry tapped 1/2" NPT





Main

| | |
|-------------------------------|--|
| Range of product | Preventa Safety detection |
| Product or component type | Safety limit switch |
| Component name | XCSD |
| Design | Compact |
| Material | Metal |
| Head type | Plunger head |
| Protection technology | Plastic protective cover, secured by 5-lobe socket head safety screw |
| Type of operator | Steel roller plunger |
| Contacts type and composition | 1 NC + 1 NC + 1 NO |
| Contacts operation | Slow-break, break before make |
| Cable entry | 1 entry tapped 1/2" NPT |

Complementary

| | |
|--|--|
| Electrical connection | Terminal |
| Clamping connection capacity | 1 x 0.34...2 x 0.75 mm ² |
| Switch actuation | By 30° cam |
| Number of poles | 3 |
| Positive opening | With NC contact |
| Mechanical durability | 10000000 cycles |
| Minimum force for tripping | 12 N |
| Positive opening minimum force | 36 N |
| Maximum actuation speed | 0.5 m/s |
| Contact code designation | R300, DC-13 (U _e = 250 V, I _e = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A B300, AC-15 (U _e = 240 V, I _e = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A |
| [I _{th}] conventional enclosed thermal current | 6 A |
| [U _i] rated insulation voltage | 400 V (degree of pollution: 3) conforming to EN/IEC 60947-1 300 V conforming to UL 508 300 V conforming to CSA C22-2 No 14 |
| [U _{imp}] rated impulse withstand voltage | 4 kV conforming to IEC 60664 4 kV conforming to EN/IEC 60947-1 |
| Resistance across terminals | <= 25 MOhm conforming to IEC 60255-7 category 3 |
| Short circuit protection | 6 A cartridge fuse type gG (gl) |
| Repeat accuracy | 0.1 mm on tripping points, 1 million operating cycles for head with end plunger |
| Body material | Zamak |
| Head material | Zamak |
| Enclosure material | Plastic |
| CAD overall width | 34 mm |
| CAD overall height | 100 mm |
| CAD overall depth | 35 mm |
| Product weight | 0.255 kg |

Environment

| | |
|--|--|
| Standards | CSA C22-2 No 14 EN 1088/ISO 14119 EN/IEC 60204-1 EN/IEC 60947-5-1 UL 508 |
| Product certifications | CSA UL |
| Safety level | Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to IEC 61508 Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1 Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1 |
| Safety reliability data | B10d = 50000000 (value given for a life time of 20 years limited by mechanical or contact wear) |
| Protective treatment | TC |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 25 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn for 11 ms conforming to IEC 60068-2-27 |
| Class of protection against electric shock | Class I conforming to NF C 20-030 Class I conforming to IEC 6140 |
| IP degree of protection | IP67 conforming to IEC 60529 IP66 conforming to IEC 60529 |
| IK degree of protection | IK06 conforming to EN 50102 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| ROHS | Compliant - since 1037 - download declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |